

# Package ‘clusterSim’

July 20, 2020

**Title** Searching for Optimal Clustering Procedure for a Data Set

**Version** 0.49-1

**Date** 2020-07-20

**Author** Marek Walesiak <marek.walesiak@ue.wroc.pl>, Andrzej Dudek <andrzej.dudek@ue.wroc.pl>

**Maintainer** Andrzej Dudek <andrzej.dudek@ue.wroc.pl>

**Depends** R (>= 3.5.0), cluster, MASS

**Imports** ade4, e1071, rgl, R2HTML, grDevices, graphics, stats, utils

**Suggests** mlbench, testthat

**Description** Distance measures (GDM1, GDM2, Sokal-Michener, Bray-Curtis, for symbolic interval-valued data), cluster quality indices (Calinski-Harabasz, Baker-Hubert, Hubert-Levine, Silhouette, Krzanowski-Lai, Hartigan, Gap, Davies-Bouldin), data normalization formulas (metric data, interval-valued symbolic data), data generation (typical and non-typical data), HI-NoV method, replication analysis, linear ordering methods, spectral clustering, agreement indices between two partitions, plot functions (for categorical and symbolic interval-valued data). (MILLIGAN, G.W., COOPER, M.C. (1985) <doi:10.1007/BF02294245>, HUBERT, L., ARABIE, P. (1985) <doi:10.1007/BF01908075>, RAND, W.M. (1971) <doi:10.1080/01621459.1971.10482356>, JAJUGA, K., WALESIAK, M. (2000) <doi:10.1007/978-3-642-57280-7\_11>, MILLIGAN, G.W., COOPER, M.C. (1988) <doi:10.1007/BF01897163>, JAJUGA, K., WALESIAK, M., BAK, A. (2003) <doi:10.1007/978-3-642-55721-7\_12>, DAVIES, D.L., BOULDIN, D.W. (1979) <doi:10.1109/TPAMI.1979.4766909>, CALINSKI, T., HARABASZ, J. (1974) <doi:10.1080/03610927408827101>, HUBERT, L. (1974) <doi:10.1080/01621459.1974.10480191>, TIBSHIRANI, R., WALTHER, G., HASTIE, T. (2001) <doi:10.1111/1467-9868.00293>, BRECKENRIDGE, J.N. (2000) <doi:10.1207/S15327906MBR3502\_5>, WALESIAK, M., DUDEK, A. (2008) <doi:10.1007/978-3-540-78246-9\_11>).

**License** GPL (>= 2)

**URL** <http://keii.ue.wroc.pl/clusterSim>

**Encoding** UTF-8

**NeedsCompilation** yes

**Repository** CRAN

**Date/Publication** 2020-07-20 20:20:03 UTC

**R topics documented:**

cluster.Description	3
cluster.Gen	4
cluster.Sim	8
comparing.Partitions	10
data.Normalization	12
data_binary	14
data_interval	14
data_mixed	15
data_nominal	15
data_ordinal	16
data_patternGDM1	16
data_patternGDM2	18
data_ratio	19
data_symbolic	20
data_symbolic_interval_polish_voivodships	20
dist.BC	21
dist.GDM	22
dist.SM	24
dist.Symbolic	25
HINoV.Mod	26
HINoV.Symbolic	28
index.C	30
index.DB	32
index.G1	34
index.G2	36
index.G3	37
index.Gap	39
index.H	42
index.KL	45
index.S	47
initial.Centers	49
interval_normalization	50
ordinalToMetric	52
pattern.GDM1	53
pattern.GDM2	57
plotCategorical	60
plotCategorical3d	61
plotInterval	62
replication.Mod	63
shapes.blocks3d	66
shapes.circles2	67
shapes.circles3	68
shapes.two.moon	70
shapes.worms	71
speccl	72

---

cluster.Description    *Descriptive statistics calculated separately for each cluster and variable*

---

### Description

Descriptive statistics calculated separately for each cluster and variable: arithmetic mean and standard deviation, median and median absolute deviation, mode

### Usage

```
cluster.Description(x, cl, sdType="sample",precision=4,modeAggregationChar=";")
```

### Arguments

x	matrix or dataset
cl	a vector of integers indicating the cluster to which each object is allocated
sdType	type of standard deviation: for "sample" (n-1) or for "population" (n)
precision	Number of digits on the right side of decimal mark sign
modeAggregationChar	Character used for aggregation of mode values (if more than one value of mode appear in variable)

### Value

Three-dimensional array:

First dimension contains cluster number

Second dimension contains original coordinate (variable) number from matrix or data set

Third dimension contains number from 1 to 5:

1 - arithmetic mean

2 - standard deviation

3 - median

4 - median absolute deviation (mad)

5 - mode (value of the variable which has the largest observed frequency. This formula is applicable for nominal and ordinal data only).

For example:

```
desc<-cluster.Description(x,cl)
```

```
desc[2,4,2] - standard deviation of fourth coordinate of second cluster
```

```
desc[3,1,5] - mode of first coordinate (variable) of third cluster
```

```
desc[1,,] - all statistics for all dimensions (variables) of first cluster
```

```
desc[,3] - medians of all dimensions (variables) for each cluster
```

**Author(s)**

Marek Walesiak <marek.walesiak@ue.wroc.pl>, Andrzej Dudek <andrzej.dudek@ue.wroc.pl>

Department of Econometrics and Computer Science, University of Economics, Wrocław, Poland

<http://keii.ue.wroc.pl/clusterSim>

**See Also**

[cluster.Sim](#), [mean](#), [sd](#), [median](#), [mad](#)

**Examples**

```
library(clusterSim)
data(data_ratio)
cl <- pam(data_ratio,5)
desc <- cluster.Description(data_ratio,cl$cluster)
print(desc)
```

---

cluster.Gen

*Random cluster generation with known structure of clusters*

---

**Description**

Random cluster generation with known structure of clusters (optionally with noisy variables and outliers)

**Usage**

```
cluster.Gen(numObjects=50, means=NULL, cov=NULL, fixedCov=TRUE,
            model=1, dataType="m", numCategories=NULL,
            numNoisyVar=0, numOutliers=0, rangeOutliers=
            c(1,10), inputType="csv2", inputHeader=TRUE,
            inputRowNames=TRUE, outputCsv="", outputCsv2="",
            outputColNames=TRUE, outputRowNames=TRUE)
```

**Arguments**

numObjects	number of objects in each cluster - positive integer value or vector with the same size as <i>nrow(means)</i> , e.g. <code>numObjects=c(50,20)</code>
means	matrix of cluster means (e.g. <code>means=matrix(c(0,8,0,8),2,2)</code> ). If <code>means = NULL</code> matrix should be read from <code>means\_&lt;modelNumber&gt;.csv file</code>
cov	covariance matrix (the same for each cluster, e.g. <code>cov=matrix(c(1,0,0,1),2,2)</code> ). If <code>cov=NULL</code> matrix should be read from <code>cov\_&lt;modelNumber&gt;.csv file</code> . Note: you cannot use this argument for generation of clusters with different covariance matrices. Those kind of generation should be done by setting <code>fixedCov</code> to <code>FALSE</code> and using appropriate model

model	<p>model number, model=1 - no cluster structure. Observations are simulated from uniform distribution over the unit hypercube in number of dimensions (variables) given in numNoisyVar argument;</p> <p>model=2 - means and covariances are taken from arguments means and cov (see Example 1);</p> <p>model=3, 4, . . . , 20 - see file  <code>\\$R\_HOME\library\clusterSim\pdf\clusterGen\_details.pdf</code>;</p> <p>model=21, 22, . . . - if fixedCov=TRUE means should be read from <code>means\_&lt;modelName&gt;.csv</code> and covariance matrix for all clusters should be read from <code>cov\_&lt;modelName&gt;.csv</code> and if fixedCov=FALSE means should be read from <code>means\_&lt;modelName&gt;.csv</code> and covariance matrices should be read separately for each cluster from <code>cov\_&lt;modelName&gt;\_&lt;clusterNumber&gt;.csv</code></p>
fixedCov	<p>if fixedCov=TRUE covariance matrix for all clusters is the same and if fixedCov=FALSE each cluster is generated from different covariance matrix - see model</p>
dataType	"m" - metric (ratio, interval), "o" - ordinal, "s" - symbolic interval
numCategories	number of categories (for ordinal data only). Positive integer value or vector with the same size as <code>ncol(means)</code> plus number of noisy variables.
numNoisyVar	number of noisy variables. For model=1 it means number of variables
numOutliers	number of outliers (for metric and symbolic interval data only). If a positive integer - number of outliers, if value from $<0,1>$ - percentage of outliers in whole data set
rangeOutliers	range for outliers (for metric and symbolic interval data only). The default range is [1, 10]. The outliers are generated independently for each variable for the whole data set from uniform distribution. The generated values are randomly added to maximum of $j$ -th variable or subtracted from minimum of $j$ -th variable
inputType	"csv" - a dot as decimal point or "csv2" - a comma as decimal point in <code>means\_&lt;modelName&gt;.csv</code> and <code>cov\_&lt;modelName&gt;.csv</code> files
inputHeader	inputHeader=TRUE indicates that input files ( <code>means\_&lt;modelName&gt;.csv</code> ; <code>cov\_&lt;modelName...&gt;.csv</code> ) contain header row
inputRowNames	inputRowNames=TRUE indicates that input files ( <code>means\_&lt;modelName&gt;.csv</code> ; <code>cov\_&lt;modelName...&gt;.csv</code> ) contain first column with row names or with number of objects (positive integer values)
outputCsv	optional, name of csv file with generated data (first column contains id, second - number of cluster and others - data)
outputCsv2	optional, name of csv (a comma as decimal point and a semicolon as field separator) file with generated data (first column contains id, second - number of cluster and others - data)
outputColNames	outputColNames=TRUE indicates that output file (given by outputCsv and outputCsv2 parameters) contains first row with column names
outputRowNames	outputRowNames=TRUE indicates that output file (given by outputCsv and outputCsv2 parameters) contains a vector of row names

**Details**

See file `\\$R_HOME\library\clusterSim\pdf\clusterGen\_details.pdf` for further details

**Value**

clusters	cluster number for each object, for model=1 each object belongs to its own cluster thus this variable contains objects numbers
data	generated data: for metric and ordinal data - matrix with objects in rows and variables in columns; for symbolic interval data three-dimensional structure: first dimension represents object number, second - variable number and third dimension contains lower- and upper-bounds of intervals

**Author(s)**

Marek Walesiak <marek.walesiak@ue.wroc.pl>, Andrzej Dudek <andrzej.dudek@ue.wroc.pl>  
 Department of Econometrics and Computer Science, University of Economics, Wrocław, Poland  
<http://keii.ue.wroc.pl/clusterSim>

**References**

- Billard, L., Diday, E. (2006), *Symbolic data analysis. Conceptual statistics and data mining*, Wiley, Chichester. ISBN: 978-0-470-09016-9.
- Qiu, W., Joe, H. (2006), *Generation of random clusters with specified degree of separation*, "Journal of Classification", vol. 23, 315-334. Available at: <http://dx.doi.org/10.1007/s00357-006-0018-y>.
- Steinley, D., Henson, R. (2005), *OCCLUS: an analytic method for generating clusters with known overlap*, "Journal of Classification", vol. 22, 221-250. Available at: <http://dx.doi.org/10.1007/s00357-005-0015-6>.
- Walesiak, M., Dudek, A. (2008), *Identification of noisy variables for nonmetric and symbolic data in cluster analysis*, In: C. Preisach, H. Burkhardt, L. Schmidt-Thieme, R. Decker (Eds.), *Data analysis, machine learning and applications*, Springer-Verlag, Berlin, Heidelberg, 85-92. Available at: [http://keii.ue.wroc.pl/pracownicy/mw/2008\\_Walesiak\\_Dudek\\_Springer.pdf](http://keii.ue.wroc.pl/pracownicy/mw/2008_Walesiak_Dudek_Springer.pdf).
- Walesiak, M. (2016), *Uogólniona miara odległości GDM w statystycznej analizie wielowymiarowej z wykorzystaniem programu R. Wydanie 2 poprawione i rozszerzone [The Generalized Distance Measure GDM in multivariate statistical analysis with R]*, Wydawnictwo Uniwersytetu Ekonomicznego, Wrocław. Available at: [http://keii.ue.wroc.pl/pracownicy/mw/2016\\_Walesiak\\_Uogolniona\\_miara\\_odleglosci\\_GDM.pdf](http://keii.ue.wroc.pl/pracownicy/mw/2016_Walesiak_Uogolniona_miara_odleglosci_GDM.pdf).

**Examples**

```
# Example 1
library(clusterSim)
means <- matrix(c(0,7,0,7),2,2)
cov <- matrix(c(1,0,0,1),2,2)
grnd <- cluster.Gen(numObjects=60,means=means,cov=cov,model=2,
numOutliers=8)
colornames <- c("red","blue","green")
```

```

grnd$clusters[grnd$clusters==0]<-length(colornames)
plot(grnd$data,col=colornames[grnd$clusters],ask=TRUE)

# Example 2
library(clusterSim)
grnd <- cluster.Gen(50,model=4,dataType="m",numNoisyVar=2)
data <- as.matrix(grnd$data)
colornames <- c("red","blue","green")
plot(grnd$data,col=colornames[grnd$clusters],ask=TRUE)

# Example 3
library(clusterSim)
grnd<-cluster.Gen(50,model=4,dataType="o",numCategories=7, numNoisyVar=2)
plotCategorical(grnd$data,,grnd$clusters,ask=TRUE)

# Example 4 (1 nonnoisy variable and 2 noisy variables, 3 clusters)
library(clusterSim)
grnd <- cluster.Gen(c(40,60,20), model=2, means=c(2,14,25),
cov=c(1.5,1.5,1.5),numNoisyVar=2)
colornames <- c("red","blue","green")
plot(grnd$data,col=colornames[grnd$clusters],ask=TRUE)

# Example 5
library(clusterSim)
grnd <- cluster.Gen(c(20,35,20,25),model=14,dataType="m",numNoisyVar=1,
fixedCov=FALSE, numOutliers=0.1)
# or
#grnd <- cluster.Gen(c(20,35,20,25),model=14,dataType="m",numNoisyVar=1,
#fixedCov=FALSE, numOutliers=0.1, outputCsv2="data14.csv")
data <- as.matrix(grnd$data)
colornames <- c("red","blue","green","brown","black")
grnd$clusters[grnd$clusters==0]<-length(colornames)
plot(grnd$data,col=colornames[grnd$clusters],ask=TRUE)

# Example 6 (this example needs files means_24.csv)
# and cov_24.csv to be placed in working directory
# library(clusterSim)
# grnd<-cluster.Gen(c(50,80,20),model=24,dataType="m",numNoisyVar=1,
# numOutliers=10, rangeOutliers=c(1,5))
# print(grnd)
# data <- as.data.frame(grnd$data)
# colornames<-c("red","blue","green","brown")
# grnd$clusters[grnd$clusters==0]<-length(colornames)
# plot(data,col=colornames[grnd$clusters],ask=TRUE)

# Example 7 (this example needs files means_25.csv and cov_25_1.csv)
# cov_25_2.csv, cov_25_3.csv, cov_25_4.csv, cov_25_5.csv
# to be placed in working directory
# library(clusterSim)
# grnd<-cluster.Gen(c(40,30,20,35,45),model=25,numNoisyVar=3,fixedCov=F)
# data <- as.data.frame(grnd$data)
# colornames<-c("red","blue","green","magenta","brown")
# plot(data,col=colornames[grnd$clusters],ask=TRUE)

```

cluster.Sim

*Determination of optimal clustering procedure for a data set***Description**

Determination of optimal clustering procedure for a data set by varying all combinations of normalization formulas, distance measures, and clustering methods

**Usage**

```
cluster.Sim (x,p,minClusterNo,maxClusterNo,icq="S",outputHtml="",
outputCsv="",outputCsv2="",normalizations=NULL,
distances=NULL,methods=NULL)
```

**Arguments**

x	matrix or dataset
p	path of simulation: 1 - ratio data, 2 - interval or mixed (ratio & interval) data, 3 - ordinal data, 4 - nominal data, 5 - binary data, 6 - ratio data without normalization, 7 - interval or mixed (ratio & interval) data without normalization, 8 - ratio data with k-means, 9 - interval or mixed (ratio & interval) data with k-means
minClusterNo	minimal number of clusters, between 2 and no. of objects - 1 (for G3 or C: no. of objects - 2)
maxClusterNo	maximal number of clusters, between 2 and no. of objects - 1 (for G3 or C: no. of objects - 2; for KL: no. of objects - 3), greater or equal minClusterNo
icq	Internal cluster quality index, "S" - Silhouette,"G1" - Calinski & Harabasz index, "G2" - Baker & Hubert index ,"G3" - G3 index,"C" - C index, "KL" - Krzanowski & Lai index
outputHtml	optional, name of html file with results
outputCsv	optional, name of csv file with results
outputCsv2	optional, name of csv (comma as decimal point sign) file with results
normalizations	optional, vector of normalization formulas that should be used in procedure
distances	optional, vector of distance measures that should be used in procedure
methods	optional, vector of classification methods that should be used in procedure

**Details**

Parameter normalizations for each path may be the subset of the following values

path 1: "n6" to "n11" (if measurement scale of variables is ratio and transformed measurement scale of variables is ratio) or "n1" to "n5" (if measurement scale of variables is ratio and transformed measurement scale of variables is interval)

path 2: "n1" to "n5"

path 3 to 7 : "n0"



path 8: "n1" to "n11"

path 9: "n1" to "n5"

Parameter distances for each path may be the subset of the following values

path 1: "d1" to "d7" (if measurement scale of variables is ratio and transformed measurement scale of variables is ratio) or "d1" to "d5" (if measurement scale of variables is ratio and transformed measurement scale of variables is interval)

path 2: "d1" to "d5"

path 3: "d8"

path 4: "d9"

path 5: "b1" to "b10"

path 6: "d1" to "d7"

path 7: "d1" to "d5"

path 8 and 9: N.A.

Parameter methods for each path may be the subset of the following values

path 1 to 7 : "m1" to "m8"

path 8: "m9"

path 9: "m9"

See file [../doc/clusterSim\\_details.pdf](#) for further details

## Value

result	optimal value of icq for all classifications
normalization	normalization used to obtain optimal value of icq
distance	distance measure used to obtain optimal value of icq
method	clustering method used to obtain optimal value of icq
classes	number of clusters for optimal value of icq
time	time of all calculations for path

## Author(s)

Marek Walesiak <marek.walesiak@ue.wroc.pl>, Andrzej Dudek <andrzej.dudek@ue.wroc.pl>

Department of Econometrics and Computer Science, University of Economics, Wrocław, Poland  
<http://keii.ue.wroc.pl/clusterSim>

## References

- Everitt, B.S., Landau, E., Leese, M. (2001), *Cluster analysis*, Arnold, London. ISBN 9780340761199.
- Gatnar, E., Walesiak, M. (Eds.) (2004), *Metody statystycznej analizy wielowymiarowej w badaniach marketingowych [Multivariate statistical analysis methods in marketing research]*, Wydawnictwo AE, Wrocław, p. 338. Available at: [http://keii.ue.wroc.pl/pracownicy/mw/2004\\_Gatnar\\_Walesiak\\_Metody\\_SAW\\_w\\_badaniach\\_marketingowych.pdf](http://keii.ue.wroc.pl/pracownicy/mw/2004_Gatnar_Walesiak_Metody_SAW_w_badaniach_marketingowych.pdf).
- Gordon, A.D. (1999), *Classification*, Chapman & Hall/CRC, London. ISBN 9781584880134.

Milligan, G.W., Cooper, M.C. (1985), *An examination of procedures of determining the number of cluster in a data set*, "Psychometrika", vol. 50, no. 2, 159-179. Available at: <https://dx.doi.org/10.1007/BF02294245>.

Milligan, G.W., Cooper, M.C. (1988), *A study of standardization of variables in cluster analysis*, "Journal of Classification", vol. 5, 181-204. Available at: <https://dx.doi.org/10.1007/BF01897163>.

Walesiak, M., Dudek, A. (2006), *Symulacyjna optymalizacja wyboru procedury klasyfikacyjnej dla danego typu danych - oprogramowanie komputerowe i wyniki badan*, Prace Naukowe AE we Wroclawiu, 1126, 120-129. Available at: [http://keii.ue.wroc.pl/pracownicy/mw/2006\\_Walesiak\\_Dudek\\_Taksonomia\\_13\\_PN\\_AE\\_1126.pdf](http://keii.ue.wroc.pl/pracownicy/mw/2006_Walesiak_Dudek_Taksonomia_13_PN_AE_1126.pdf).

Walesiak, M., Dudek, A. (2007), *Symulacyjna optymalizacja wyboru procedury klasyfikacyjnej dla danego typu danych - charakterystyka problemu*, Zeszyty Naukowe Uniwersytetu Szczecinskiego nr 450, 635-646. Available at: [http://keii.ue.wroc.pl/pracownicy/mw/2007\\_Walesiak\\_Dudek\\_Symulacyjna\\_optymalizacja\\_wyboru.pdf](http://keii.ue.wroc.pl/pracownicy/mw/2007_Walesiak_Dudek_Symulacyjna_optymalizacja_wyboru.pdf).

### See Also

[data.Normalization](#), [dist.GDM](#), [dist.BC](#), [dist.SM](#), [index.G1](#), [index.G2](#), [index.G3](#), [index.C](#), [index.S](#), [index.KL](#), [hclust](#), [dist](#),

### Examples

```
library(clusterSim)
# Commented due to long execution time
#data(data_ratio)
#cluster.Sim(data_ratio, 1, 2, 3, "G1", outputCsv="results1")
#data(data_interval)
#cluster.Sim(data_interval, 2, 2, 4, "G1", outputHtml="results2")
#data(data_ordinal)
#cluster.Sim(data_ordinal, 3, 2, 4, "G2", outputCsv2="results3")
#data(data_nominal)
#cluster.Sim(data_nominal, p=4, 2, 4, icq="G3", outputHtml="results4", methods=c("m2", "m3", "m5"))
#data(data_binary)
#cluster.Sim(data_binary, p=5, 2, 4, icq="S", outputHtml="results5", distances=c("b1", "b3", "b6"))
#data(data_ratio)
#cluster.Sim(data_ratio, 1, 2, 4, "G1", outputCsv="results6", normalizations=c("n1", "n3"),
#distances=c("d2", "d5"), methods=c("m5", "m3", "m1"))
```

---

comparing.Partitions *Calculate agreement indices between two partitions*

---

### Description

Calculate agreement indices between two partitions

### Usage

```
comparing.Partitions(c11, c12, type="nowak")
```

**Arguments**

c11	A vector of integers (or letters) indicating the cluster to which each object is allocated for first clustering
c12	A vector of integers (or letters) indicating the cluster to which each object is allocated for second clustering
type	"rand" - for Rand index, "crand" - for adjusted Rand index or "nowak" for Nowak index

**Details**

See file `\$R\_HOME\library\clusterSim\pdf\comparingPartitions\_details.pdf` for further details.

Rand and adjusted Rand indices uses `classAgreement` function from `e1071` library.

**Value**

Returns value of index.

**Author(s)**

Marek Walesiak <marek.walesiak@ue.wroc.pl>, Andrzej Dudek <andrzej.dudek@ue.wroc.pl>  
Department of Econometrics and Computer Science, University of Economics, Wrocław, Poland  
<http://keii.ue.wroc.pl/clusterSim>

**References**

Hubert, L., Arabie, P. (1985), *Comparing partitions*, "Journal of Classification", no. 1, 193-218.  
Available at: <http://dx.doi.org/10.1007%2FBF01908075>.

Nowak, E. (1985), *Wskaznik podobienstwa wynikow podzialow*, "Przegląd Statystyczny" ["Statistical Review"], no. 1, 41-48.

Rand, W.M. (1971), *Objective criteria for the evaluation of clustering methods*, "Journal of the American Statistical Association", no. 336, 846-850. Available at: <http://dx.doi.org/10.1080/01621459.1971.10482356>.

**See Also**

[replication.Mod](#)

**Examples**

```
# Example 1
library(clusterSim)
dataSet<-cluster.Gen(model=5)
c11<-dataSet$clusters
c12<-kmeans(dataSet$data,2)$cluster
print(comparing.Partitions(c11,c12,type="rand"))

# Example 2
library(clusterSim)
```

```

data(data_patternGDM1)
z<-data.Normalization(data_patternGDM1,type="n1")
d<-dist.GDM(z,method="GDM1")
c11<-pam(d,3,diss=TRUE)$clustering
c12<-pam(d,4,diss=TRUE)$clustering
print(comparing.Partitions(c11,c12,type="crand"))

# Example 3
library(clusterSim)
data(data_patternGDM1)
z<-data.Normalization(data_patternGDM1,type="n9")
d<-dist.GDM(z,method="GDM1")
c11<-pam(d,3,diss=TRUE)$clustering
hc<-hclust(d,method="complete")
c12<-cutree(hc,k=3)
print(comparing.Partitions(c11,c12,type="nowak"))

```

---

data.Normalization      *Types of variable (column) and object (row) normalization formulas*

---

### Description

Types of variable (column) and object (row) normalization formulas

### Usage

```
data.Normalization (x,type="n0",normalization="column",...)
```

### Arguments

x	vector, matrix or dataset
type	type of normalization: n0 - without normalization n1 - standardization $((x-\text{mean})/\text{sd})$ n2 - positional standardization $((x-\text{median})/\text{mad})$ n3 - unitization $((x-\text{mean})/\text{range})$ n3a - positional unitization $((x-\text{median})/\text{range})$ n4 - unitization with zero minimum $((x-\text{min})/\text{range})$ n5 - normalization in range $<-1,1>$ $((x-\text{mean})/\text{max}(\text{abs}(x-\text{mean})))$ n5a - positional normalization in range $<-1,1>$ $((x-\text{median})/\text{max}(\text{abs}(x-\text{median})))$ n6 - quotient transformation $(x/\text{sd})$ n6a - positional quotient transformation $(x/\text{mad})$ n7 - quotient transformation $(x/\text{range})$ n8 - quotient transformation $(x/\text{max})$ n9 - quotient transformation $(x/\text{mean})$ n9a - positional quotient transformation $(x/\text{median})$ n10 - quotient transformation $(x/\text{sum})$

n11 - quotient transformation ( $x/\sqrt{SSQ}$ )  
 n12 - normalization ( $(x-\text{mean})/\sqrt{\text{sum}((x-\text{mean})^2)}$ )  
 n12a - positional normalization ( $(x-\text{median})/\sqrt{\text{sum}((x-\text{median})^2)}$ )  
 n13 - normalization with zero being the central point ( $(x-\text{midrange})/(\text{range}/2)$ )  
 normalization "column" - normalization by variable, "row" - normalization by object  
 ... arguments passed to sum, mean, min sd, mad and other aggregation functions.  
 In particular: na.rm - a logical value indicating whether NA values should be stripped before the computation

### Details

See file [../doc/dataNormalization\\_details.pdf](#) for further details

### Value

Normalized data The numeric shifts and scalings used (if any) are returned as attributes "normalized:shift" and "normalized:scale"

### Author(s)

Marek Walesiak <marek.walesiak@ue.wroc.pl>, Andrzej Dudek <andrzej.dudek@ue.wroc.pl>  
 Department of Econometrics and Computer Science, University of Economics, Wroclaw, Poland  
<http://keii.ue.wroc.pl/clusterSim>

### References

- Anderberg, M.R. (1973), *Cluster analysis for applications*, Academic Press, New York, San Francisco, London. ISBN 9780120576500.
- Gatnar, E., Walesiak, M. (Eds.) (2004), *Metody statystycznej analizy wielowymiarowej w badaniach marketingowych [Multivariate statistical analysis methods in marketing research]*, Wydawnictwo AE, Wroclaw, 35-38. Available at: [http://keii.ue.wroc.pl/pracownicy/mw/2004\\_Gatnar\\_Walesiak\\_Metody\\_SAW\\_w\\_badaniach\\_marketingowych.pdf](http://keii.ue.wroc.pl/pracownicy/mw/2004_Gatnar_Walesiak_Metody_SAW_w_badaniach_marketingowych.pdf).
- Jajuga, K., Walesiak, M. (2000), *Standardisation of data set under different measurement scales*, In: R. Decker, W. Gaul (Eds.), *Classification and information processing at the turn of the millennium*, Springer-Verlag, Berlin, Heidelberg, 105-112. Available at: [http://dx.doi.org/10.1007/978-3-642-57280-7\\_11](http://dx.doi.org/10.1007/978-3-642-57280-7_11).
- Milligan, G.W., Cooper, M.C. (1988), *A study of standardization of variables in cluster analysis*, "Journal of Classification", vol. 5, 181-204. Available at: <https://dx.doi.org/10.1007/BF01897163>.
- Młodak, A. (2006), *Analiza taksonomiczna w statystyce regionalnej*, Difin, Warszawa. ISBN 83-7251-605-7.
- Walesiak, M. (2014), *Przegląd formuł normalizacji wartości zmiennych oraz ich własności w statystycznej analizie wielowymiarowej [Data normalization in multivariate data analysis. An overview and properties]*, "Przegląd Statystyczny" ("Statistical Review"), vol. 61, no. 4, 363-372. Available at: [http://keii.ue.wroc.pl/pracownicy/mw/2014\\_Walesiak\\_Przegląd\\_Statystyczny\\_z\\_4.pdf](http://keii.ue.wroc.pl/pracownicy/mw/2014_Walesiak_Przegląd_Statystyczny_z_4.pdf).

**See Also**[cluster.Sim](#)**Examples**

```
library(clusterSim)
data(data_ratio)
z1 <- data.Normalization(data_ratio,type="n1",normalization="column",na.rm=FALSE)
z2 <- data.Normalization(data_ratio,type="n10",normalization="row",na.rm=FALSE)
```

---

`data_binary`*Binary data*

---

**Description**

Binary variables for eight people

**Format**

data.frame: 8 objects, 10 variables

**Source**

Kaufman, L., Rousseeuw, P.J. (1990), *Finding groups in data: an introduction to cluster analysis*, Wiley, New York, p. 24.

**Examples**

```
#library(clusterSim)
#data(data_binary)
#cluster.Sim(data_binary, p=5, 2, 6, icq="S",
#outputHtml="results5", distances=c("b1", "b3", "b6"))
```

---

`data_interval`*Interval data*

---

**Description**

Artificially generated interval data

**Format**

data.frame: 75 objects, 5 variables, 5-class structure

**Source**

Artificially generated data

**Examples**

```
#library(clusterSim)
#data(data_interval)
#cluster.Sim(data_interval, 2, 2, 3, "G1", outputHtml="results2")
```

---

data\_mixed

*Mixed data*


---

**Description**

Artificial mixed data

**Format**

data.frame: 25 objects, 4 variables (1, 3 - interval variables, 2 - ordinal variable, 4, nominal variable)

**Source**

Artificial data

**Examples**

```
library(clusterSim)
data(data_mixed)
r3 <- HINoV.Mod(data_mixed, type=c("m","n","m","n"), s=2, 3, distance="d1",
  method="complete", Index="cRAND")
print(r3$stopri)
plot(r3$stopri[,2], xlab="Variable number", ylab="topri", xaxt="n")
axis(1,at=c(1:max(r3$stopri[,1])),labels=r3$stopri[,1])
```

---

data\_nominal

*Nominal data*


---

**Description**

Artificial nominal data

**Format**

data.frame: 26 objects, 12 variables

**Source**

Artificial data

**Examples**

```
#library(clusterSim)
#data(data_nominal)
#cluster.Sim(data_nominal, p=4, 2, 5, icq="G3",
#outputHtml="results4", methods=c("m2", "m3", "m5"))
```

---

data\_ordinal

*Ordinal data*


---

**Description**

Artificial ordinal data

**Format**

data.frame: 26 objects, 12 variables

**Source**

Artificial data

**Examples**

```
#library(clusterSim)
#data(data_ordinal)
#cluster.Sim(data_ordinal, 3, 3, 12, "S",
#outputCsv2="results3")
```

---

data\_patternGDM1

*Metric data with 17 objects and 10 variables (8 stimulant variables, 2 destimulant variables)*


---

**Description**

Metric data with 17 objects and 10 variables (8 stimulant variables, 2 destimulant variables)

Data on the Polish voivodships, owing to the conditions of the population living in cities in 2007. The analysis includes the following variables:

x1 - dwellings in per cent fitted with water-line system,

x2 - dwellings in per cent fitted with lavatory,

x3 - dwellings in per cent fitted with bathroom,

x4 - dwellings in per cent fitted with gas-line system,

x5 - dwellings in per cent fitted with central heating,

x6 - average number of rooms per dwelling,



x7 - average number of persons per dwelling,  
 x8 - average number of persons per room,  
 x9 - usable floor space in square meter per dwelling,  
 x10 - usable floor space in square meter per person.

Types of performance variables:

x1 - x6, x9, x10 - stimulants,  
 x7, x8 - destimulants.

### Format

data.frame: 17 objects, 10 variables

### Source

Voivodships Statistical Yearbook, Poland 2008.

### Examples

```
# Example 1
library(clusterSim)
data(data_patternGDM1)
res<-pattern.GDM1(data_patternGDM1,
performanceVariable=c("s","s","s","s","s","s","d","d","s","s"),
scaleType="r",nomOptValues=NULL,weightsType<-"equal",weights=NULL,
normalization<-"n4",patternType<-"lower",patternCoordinates<-"manual",
patternManual<-c(0,0,0,0,0,"min","max","max","min","min"),
nominalTransfMethod <-NULL)
print(res)
gdm_p<-res$distances
plot(cbind(gdm_p,gdm_p),xlim=c(max(gdm_p),min(gdm_p)),
ylim=c(min(gdm_p),max(gdm_p)),xaxt="n",
xlab="Order of objects from the best to the worst",
ylab="GDM distances from pattern object",lwd=1.6)
axis(1, at=gdm_p,labels=names(gdm_p), cex.axis=0.5)

# Example 2
library(clusterSim)
data(data_patternGDM1)
res<-pattern.GDM1(data_patternGDM1,
performanceVariable=c("s","s","s","s","s","s","d","d","s","s"),
scaleType="r",nomOptValues=NULL,weightsType<-"equal",weights=NULL,
normalization<-"n2",patternType<-"upper",
patternCoordinates<-"dataBounds",patternManual<-NULL,
nominalTransfMethod <-NULL)
print(res)
gdm_p<-res$distances
plot(cbind(gdm_p,gdm_p),xlim=c(min(gdm_p),max(gdm_p)),
ylim=c(min(gdm_p),max(gdm_p)),xaxt="n",
xlab="Order of objects from the best to the worst",
ylab="GDM distances from pattern object", lwd=1.6)
```

```
axis(1, at=gdm_p, labels=names(gdm_p), cex.axis=0.5)
```

---

data_patternGDM2	<i>Ordinal data with 27 objects and 6 variables (3 stimulant variables, 2 destimulant variables and 1 nominant variable)</i>
------------------	--

---

### Description

Ordinal data with 27 objects and 6 variables (3 stimulant variables, 2 destimulant variables and 1 nominant variable)

Residential housing properties were described by the following variables:

x1 - Location of environmental land, which is linked to a dwelling (1 - poor, 2 - inadequate, 3 - satisfactory, 4 - good, 5 - very good),

x2 - Standard utility of a dwelling (1 - bad, 2 - low, 3 - average, 4 - high),

x3 - Living conditions occurring on the land, which is linked to a dwelling (1 - bad, 2 - average, 3 - good),

x4 - Location of land, which is related to dwelling in the area of the city (1 - central, 2 - downtown, 3 - intermediate, 4 - peripheral),

x5 - Type of condominium (1 - low, 2 - large),

x6 - Area of land, which is related to dwelling (1 - below the contour of the building, 2 - outline of the building, 3 - the outline of the building with the environment acceptable, such as parking, playground, 4 - the outline of the building with the environment too much).

Types of performance variables:

x1, x2, x3 - stimulants,

x4, x5 - destimulants,

x6 - nominant (the nominal category: 3).

### Format

data.frame: 27 objects, 6 variables

### Source

data from real estate market

### Examples

```
# Example 1
library(clusterSim)
data(data_patternGDM2)
res<-pattern.GDM2(data_patternGDM2,
performanceVariable=c("s","s","s","d","d","n"),
nomOptValues=c(NA,NA,NA,NA,NA,3), weightsType<-"equal", weights=NULL,
patternType="lower", patternCoordinates="manual",
```

```

patternManual=c("min", "min", 0, 5, "max", "max"),
nominalTransfMethod="symmetrical")
print(res)
gdm_p<-res$distances
plot(cbind(gdm_p, gdm_p), xlim=c(max(gdm_p), min(gdm_p)),
ylim=c(min(gdm_p), max(gdm_p)),
xaxt="n", xlab="Order of objects from the best to the worst",
ylab="GDM distances from pattern object", lwd=1.6)
axis(1, at=gdm_p, labels=names(gdm_p), cex.axis=0.5)

# Example 2
library(clusterSim)
data(data_patternGDM2)
res<-pattern.GDM2(data_patternGDM2,
performanceVariable=c("s", "s", "s", "d", "d", "n"),
nomOptValues=c(NA, NA, NA, NA, NA, 3), weightsType<-"equal", weights=NULL,
patternType="upper", patternCoordinates="dataBounds",
patternManual=NULL, nominalTransfMethod="database")
print(res)
gdm_p<-res$distances
plot(cbind(gdm_p, gdm_p), xlim=c(min(gdm_p), max(gdm_p)),
ylim=c(min(gdm_p), max(gdm_p)),
xaxt="n", xlab="Order of objects from the best to the worst",
ylab="GDM distances from pattern object", lwd=1.6)
axis(1, at=gdm_p, labels=names(gdm_p), cex.axis=0.5)

```

---

data\_ratio

*Ratio data*


---

### Description

Artificially generated ratio data

### Format

data.frame: 75 objects, 5 variables, 5-class structure

### Source

Artificially generated data

### Examples

```

#library(clusterSim)
#data(data_ratio)
#c <- pam(data_ratio, 10)
#index.G1(data_ratio, c$clustering)

```

---

data_symbolic	<i>Symbolic interval data</i>
---------------	-------------------------------

---

**Description**

Artificially generated symbolic interval data

**Format**

3-dimensional array: 125 objects, 6 variables, third dimension represents beginning and end of interval, 5-class structure

**Source**

Artificially generated data

**Examples**

```
library(clusterSim)
data(data_symbolic)
r<- HINoV.Symbolic(data_symbolic, u=5)
print(r$stopri)
plot(r$stopri[,2], xlab="Variable number", ylab="topri",
xaxt="n", type="b")
axis(1,at=c(1:max(r$stopri[,1])),labels=r$stopri[,1])
```

---

data_symbolic_interval_polish_voivodships
---

*The evaluation of Polish voivodships tourism attractiveness level*

---

**Description**

The empirical study uses the statistical data referring to the attractiveness level of 18 objects (16 Polish NUTS-2 regions - voivodships, pattern and anti-pattern object).

Two-stage data collection was performed. Firstly, data on tourist attractiveness were collected for 380 counties using 9 classic metric variables (measured on a ratio scale):

x1 - beds in hotels per 1000 inhabitants of a county,

x2 - number of nights spent daily by resident tourists per 1000 inhabitants of a county,

x3 - number of nights spent daily by foreign tourists per 1000 inhabitants of a county,

x4 - dust pollution emission in tons per 10 km<sup>2</sup> of a county area,

x5 - gas pollution emission in tons per 1 km<sup>2</sup> of a county area,

x6 - number of criminal offences, crimes against life and health and property crimes per 1000 inhabitants of a county,

x7 - forest cover of the county in

x8 - participants of mass events per 1000 inhabitants of a county,

x9 - number of tourist economy entities (sections: I, N79) registered in the system REGON per 1000 inhabitants of a county.

The three variables (x4, x5 and x6) are destimulants. Other variables are stimulants.

In the second step, the data were aggregated to the level of the voivodships (NUTS-2), giving the symbolic interval-valued data. The lower bound of the interval for each symbolic interval-valued variable in the voivodship was obtained by calculating the first quartile on the basis of data from counties. The upper bound of the interval was obtained by calculating the third quartile.

### Format

Tree-dimensional array: 18 objects (16 Polish NUTS-2 regions - voivodships, pattern and anti-pattern object), 9 symbolic interval-valued variables with lower and upper values of interval in third dimension. The coordinates of a pattern object cover the most preferred preference variable values. The coordinates of an anti-pattern object cover the least preferred preference variable values.

### Source

The statistical data were collected in 2016 and come from the Local Data Bank of the Central Statistical Office of Poland.

### Examples

```
library(clusterSim)
data(data_symbolic_interval_polish_voivodships)
print(data_symbolic_interval_polish_voivodships)
```

---

dist.BC

*Calculates Bray-Curtis distance measure for ratio data*

---

### Description

Calculates Bray-Curtis distance measure for ratio data

### Usage

```
dist.BC (x)
```

### Arguments

x                   matrix or dataset

### Details

See file `\\$R_HOME\library\clusterSim\pdf\distBC_details.pdf` for further details

**Value**

object with calculated distance

**Author(s)**

Marek Walesiak <marek.walesiak@ue.wroc.pl>, Andrzej Dudek <andrzej.dudek@ue.wroc.pl>  
Department of Econometrics and Computer Science, University of Economics, Wrocław, Poland  
<http://keii.ue.wroc.pl/clusterSim>

**References**

Cormack, R.M. (1971), *A review of classification (with discussion)*, "Journal of the Royal Statistical Society", ser. A, part 3, 321-367.

Gatnar, E., Walesiak, M. (Eds.) (2004), *Metody statystycznej analizy wielowymiarowej w badaniach marketingowych [Multivariate statistical analysis methods in marketing research]*, Wydawnictwo AE, Wrocław, p. 41. Available at: [http://keii.ue.wroc.pl/pracownicy/mw/2004\\_Gatnar\\_Walesiak\\_Metody\\_SAW\\_w\\_badaniach\\_marketingowych.pdf](http://keii.ue.wroc.pl/pracownicy/mw/2004_Gatnar_Walesiak_Metody_SAW_w_badaniach_marketingowych.pdf).

**See Also**

[dist.GDM](#), [dist.SM](#), [dist](#)

**Examples**

```
library(clusterSim)
sampleData <- cbind(c(2,3,5),c(4,5,6),c(5,3,4))
d <- dist.BC(sampleData)
```

---

dist.GDM

*Calculates Generalized Distance Measure*

---

**Description**

Calculates Generalized Distance Measure for variables measured on metric scale (ratio & interval) or ordinal scale

**Usage**

```
dist.GDM(x, method="GDM1", weightsType="equal", weights=NULL)
GDM(x, method="GDM1", weightsType="equal", weights=NULL)
GDM1(x, weightsType="equal", weights=NULL)
GDM2(x, weightsType="equal", weights=NULL)
```

**Arguments**

x	matrix or data set
method	GDM1 or GDM2 "GDM1" - metric scale (ratio & interval) "GDM2" - ordinal scale
weightsType	equal or different1 or different2 "equal" - equal weights "different1" - vector of different weights should satisfy conditions: each weight takes value from interval [0; 1] and sum of weights equals one "different2" - vector of different weights should satisfy conditions: each weight takes value from interval [0; m] and sum of weights equals m (m - the number of variables)
weights	vector of weights

**Details**

See file `\$R\HOME\library\clusterSim\pdf\distGDM_details.pdf` for further details

**Value**

object with calculated distance

**Author(s)**

Marek Walesiak <marek.walesiak@ue.wroc.pl>, Andrzej Dudek <andrzej.dudek@ue.wroc.pl>  
Department of Econometrics and Computer Science, University of Economics, Wrocław, Poland  
<http://keii.ue.wroc.pl/clusterSim>

**References**

- Jajuga, K., Walesiak, M., Bak, A. (2003), *On the general distance measure*, In: M. Schwaiger, O. Opitz (Eds.), *Exploratory data analysis in empirical research*, Springer-Verlag, Berlin, Heidelberg, 104-109. Available at: [http://dx.doi.org/10.1007/978-3-642-55721-7\\_12](http://dx.doi.org/10.1007/978-3-642-55721-7_12).
- Walesiak, M. (1999), *Distance Measure for Ordinal Data*, "Argumenta Oeconomica", No. 2 (8), 167-173. Available at: [http://keii.ue.wroc.pl/pracownicy/mw/1999\\_Walesiak\\_Argumenta\\_Oeconomica\\_no\\_2.pdf](http://keii.ue.wroc.pl/pracownicy/mw/1999_Walesiak_Argumenta_Oeconomica_no_2.pdf).
- Walesiak, M. (2006), *Uogólniona miara odległości w statystycznej analizie wielowymiarowej [The Generalized Distance Measure in multivariate statistical analysis]*, Wydawnictwo AE, Wrocław. Available at: [http://keii.ue.wroc.pl/pracownicy/mw/2006\\_Walesiak\\_Uogolniona\\_miara\\_odleglosci.pdf](http://keii.ue.wroc.pl/pracownicy/mw/2006_Walesiak_Uogolniona_miara_odleglosci.pdf).

**See Also**

[dist.BC](#), [dist.SM](#), [dist](#)

**Examples**

```
#Example 1
library(clusterSim)
data(data_ratio)
d1 <- GDM(data_ratio, method="GDM1")
data(data_ordinal)
d2 <- GDM(data_ordinal, method="GDM2")
d3 <- GDM1(data_ratio)
d4 <- GDM2(data_ordinal)

#Example 2
library(clusterSim)
data(data_ratio)
d1w <- GDM(data_ratio, method="GDM1", weightsType="different1",
weights=c(0.4,0.1,0.3,0.15,0.05))
data(data_ordinal)
d2w <- GDM(data_ordinal, method="GDM2", weightsType="different2",
weights=c(1,3,0.5,1.5,1.8,0.2,0.4,0.6,0.2,0.4,0.9,1.5))
```

---

dist.SM

*Calculates Sokal-Michener distance measure for nominal variables*

---

**Description**

Calculates Sokal-Michener distance measure for nominal variables

**Usage**

```
dist.SM(x)
```

**Arguments**

x                   matrix or data set

**Details**

See file `\$R_HOME\library\clusterSim\pdf\distSM_details.pdf` for further details

**Value**

object with calculated distance

**Author(s)**

Marek Walesiak <marek.walesiak@ue.wroc.pl>, Andrzej Dudek <andrzej.dudek@ue.wroc.pl>  
Department of Econometrics and Computer Science, University of Economics, Wrocław, Poland  
<http://keii.ue.wroc.pl/clusterSim>



## References

Gatnar, E., Walesiak, M. (Eds.) (2004), *Metody statystycznej analizy wielowymiarowej w badaniach marketingowych [Multivariate statistical analysis methods in marketing research]*, Wydawnictwo AE, Wrocław, p. 43. Available at: [http://keii.ue.wroc.pl/pracownicy/mw/2004\\_Gatnar\\_Walesiak\\_Metody\\_SAW\\_w\\_badaniach\\_marketingowych.pdf](http://keii.ue.wroc.pl/pracownicy/mw/2004_Gatnar_Walesiak_Metody_SAW_w_badaniach_marketingowych.pdf).

Kaufman, L., Rousseeuw, P.J. (1990), *Finding groups in data: an introduction to cluster analysis*, Wiley, New York, p. 28. ISBN: 978-0-471-73578-6.

## See Also

[dist.GDM](#), [dist.BC](#), [dist](#)

## Examples

```
library(clusterSim)
data(data_nominal)
d <- dist.SM(data_nominal)
```

---

dist.Symbolic	<i>Calculates distance between interval-valued symbolic data</i>
---------------	--

---

## Description

Calculates distance between interval-valued symbolic data for four distance types

## Usage

```
dist.Symbolic(data, type="U_2", gamma=0.5, power=2)
```

## Arguments

data	symbolic data
type	type of distance used for symbolic interval-valued data U_2 - Ichino and Yaguchi distance M - distance between points given by means of intervals (for interval-values variables), H - Hausdorff distance, S - sum of distances between all corresponding vertices of hyperrectangles given by symbolic objects with interval-valued variables
gamma	parameter for calculating Ichino and Yaguchi distance
power	parameter for calculating distance: Ichino and Yaguchi distance, Hausdorff distance

**Author(s)**

Marek Walesiak <marek.walesiak@ue.wroc.pl>, Andrzej Dudek <andrzej.dudek@ue.wroc.pl>  
 Department of Econometrics and Computer Science, University of Economics, Wroclaw, Poland  
<http://keii.ue.wroc.pl/clusterSim>

**References**

- Billard, L., Diday, E. (2006), *Symbolic data analysis. Conceptual statistics and data mining*, Wiley, Chichester. ISBN: 978-0-470-09016-9.
- Ichino, M., Yaguchi, H. (1994), *Generalized Minkowski metrics for mixed feature type data analysis*, "IEEE Transactions on Systems Man and Cybernetics", Vol. 24, Issue 4, 698-708. [Http://dx.doi.org/10.1109/21.286391](http://dx.doi.org/10.1109/21.286391).

**See Also**

symbolicDA::dist.SDA

**Examples**

```
library(clusterSim)
dataSymbolic<-cluster.Gen(numObjects=10,model=5,dataType="s")$data
print(dist.Symbolic(dataSymbolic))
```

---

HINoV.Mod

*Modification of Carbone, Kara & Maxwell Heuristic Identification of Noisy Variables (HINoV) method*

---

**Description**

Modification of Heuristic Identification of Noisy Variables (HINoV) method

**Usage**

```
HINoV.Mod (x, type="metric", s = 2, u, distance=NULL,
method = "kmeans", Index ="cRAND")
```

**Arguments**

x	data matrix
type	"metric" (default) - all variables are metric (ratio, interval), "nonmetric" - all variables are nonmetric (ordinal, nominal) or vector containing for each variable value "m"(metric) or "n"(nonmetric) for mixed variables (metric and nonmetric), e.g. type=c("m", "n", "n", "m")
s	for metric data only: 1 - ratio data, 2 - interval or mixed (ratio & interval) data
u	number of clusters (for metric data only)

distance	NULL for kmeans method (based on data matrix) and nonmetric data for ratio data: "d1" - Manhattan, "d2" - Euclidean, "d3" - Chebychev (max), "d4" - squared Euclidean, "d5" - GDM1, "d6" - Canberra, "d7" - Bray-Curtis for interval or mixed (ratio & interval) data: "d1", "d2", "d3", "d4", "d5"
method	NULL for nonmetric data clustering method: "kmeans" (default), "single", "ward.D", "ward.D2", "complete", "average", "mcquitty", "median", "centroid", "pam"
Index	"cRAND" - corrected Rand index (default); "RAND" - Rand index

### Details

See file [../doc/HINoVMod\\_details.pdf](#) for further details

### Value

parim	$m \times m$ symmetric matrix ( $m$ - number of variables). Matrix contains pairwise corrected Rand (Rand) indices for partitions formed by the $j$ -th variable with partitions formed by the $l$ -th variable
topri	sum of rows of parim
stopri	ranked values of topri in decreasing order

### Author(s)

Marek Walesiak <marek.walesiak@ue.wroc.pl>, Andrzej Dudek <andrzej.dudek@ue.wroc.pl>  
Department of Econometrics and Computer Science, University of Economics, Wroclaw, Poland  
<http://keii.ue.wroc.pl/clusterSim>

### References

- Carmone, F.J., Kara, A., Maxwell, S. (1999), *HINoV: a new method to improve market segment definition by identifying noisy variables*, "Journal of Marketing Research", November, vol. 36, 501-509.
- Hubert, L.J., Arabie, P. (1985), *Comparing partitions*, "Journal of Classification", no. 1, 193-218. Available at: <http://dx.doi.org/10.1007%2FBF01908075>.
- Rand, W.M. (1971), *Objective criteria for the evaluation of clustering methods*, "Journal of the American Statistical Association", no. 336, 846-850. Available at: <http://dx.doi.org/10.1080/01621459.1971.10482356>.
- Walesiak, M. (2005), *Variable selection for cluster analysis - approaches, problems, methods*, Plenary Session of the Committee on Statistics and Econometrics of the Polish Academy of Sciences, 15 March, Wroclaw.
- Walesiak, M., Dudek, A. (2008), *Identification of noisy variables for nonmetric and symbolic data in cluster analysis*, In: C. Preisach, H. Burkhardt, L. Schmidt-Thieme, R. Decker (Eds.), *Data analysis, machine learning and applications*, Springer-Verlag, Berlin, Heidelberg, 85-92. Available at: [http://dx.doi.org/10.1007/978-3-540-78246-9\\_11](http://dx.doi.org/10.1007/978-3-540-78246-9_11)

**See Also**

[hclust](#), [kmeans](#), [dist](#), [dist.GDM](#), [dist.BC](#), [dist.SM](#), [cluster.Sim](#)

**Examples**

```
# for metric data
library(clusterSim)
data(data_ratio)
r1<- HINoV.Mod(data_ratio, type="metric", s=1, 4, method="kmeans",
  Index="cRAND")
print(r1$stopri)
plot(r1$stopri[,2],xlab="Variable number", ylab="topri",
xaxt="n", type="b")
axis(1,at=c(1:max(r1$stopri[,1])),labels=r1$stopri[,1])

# for nonmetric data
library(clusterSim)
data(data_nominal)
r2<- HINoV.Mod (data_nominal, type="nonmetric", Index = "cRAND")
print(r2$stopri)
plot(r2$stopri[,2], xlab="Variable number", ylab="topri",
xaxt="n", type="b")
axis(1,at=c(1:max(r2$stopri[,1])),labels=r2$stopri[,1])

# for mixed data
library(clusterSim)
data(data_mixed)
r3<- HINoV.Mod(data_mixed, type=c("m","n","m","n"), s=2, 3, distance="d1",
  method="complete", Index="cRAND")
print(r3$stopri)
plot(r3$stopri[,2], xlab="Variable number", ylab="topri",
xaxt="n", type="b")
axis(1,at=c(1:max(r3$stopri[,1])),labels=r3$stopri[,1])
```

---

HINoV.Symbolic

*Modification of Carmone, Kara & Maxwell Heuristic Identification of Noisy Variables (HINoV) method for symbolic interval data*

---

**Description**

Modification of Heuristic Identification of Noisy Variables (HINoV) method for symbolic interval data

**Usage**

```
HINoV.Symbolic(x, u=NULL, distance="H", method = "pam",
  Index = "cRAND")
```

**Arguments**

x	symbolic interval data: a 3-dimensional table, first dimension represents object number, second dimension - variable number, and third dimension contains lower- and upper-bounds of intervals
u	number of clusters
distance	"M" - minimal distance between all vertices of hyper-cubes defined by symbolic interval variables; "H" - Hausdorff distance; "S" - sum of squares of distance between all vertices of hyper-cubes defined by symbolic interval variables
method	clustering method: "single", "ward.D", "ward.D2", "complete", "average", "mcquitty", "median", "centroid", "pam" (default)
Index	"cRAND" - corrected Rand index (default); "RAND" - Rand index

**Details**

See file [../doc/HINoVSymbolic\\_details.pdf](#) for further details

**Value**

parim	$m \times m$ symmetric matrix ( $m$ - number of variables). Matrix contains pairwise corrected Rand (Rand) indices for partitions formed by the $j$ -th variable with partitions formed by the $l$ -th variable
topri	sum of rows of parim
stopri	ranked values of topri in decreasing order

**Author(s)**

Marek Walesiak <marek.walesiak@ue.wroc.pl>, Andrzej Dudek <andrzej.dudek@ue.wroc.pl>  
 Department of Econometrics and Computer Science, University of Economics, Wrocław, Poland  
<http://keii.ue.wroc.pl/clusterSim>

**References**

- Carmone, F.J., Kara, A., Maxwell, S. (1999), *HINoV: a new method to improve market segment definition by identifying noisy variables*, "Journal of Marketing Research", November, vol. 36, 501-509.
- Hubert, L.J., Arabie, P. (1985), *Comparing partitions*, "Journal of Classification", no. 1, 193-218. Available at: <http://dx.doi.org/10.1007%2FBF01908075>.
- Rand, W.M. (1971), *Objective criteria for the evaluation of clustering methods*, "Journal of the American Statistical Association", no. 336, 846-850. Available at: <http://dx.doi.org/10.1080/01621459.1971.10482356>.
- Walesiak, M., Dudek, A. (2008), *Identification of noisy variables for nonmetric and symbolic data in cluster analysis*, In: C. Preisach, H. Burkhardt, L. Schmidt-Thieme, R. Decker (Eds.), *Data analysis, machine learning and applications*, Springer-Verlag, Berlin, Heidelberg, 85-92. Available at: [http://keii.ue.wroc.pl/pracownicy/mw/2010\\_Walesiak\\_Dudek\\_Springer.PDF](http://keii.ue.wroc.pl/pracownicy/mw/2010_Walesiak_Dudek_Springer.PDF)

**See Also**

[hclust](#), [kmeans](#), [cluster.Sim](#)

**Examples**

```
library(clusterSim)
data(data_symbolic)
r<- HINoV.Symbolic(data_symbolic, u=5)
print(r$stopri)
plot(r$stopri[,2], xlab="Variable number", ylab="topri",
xaxt="n", type="b")
axis(1,at=c(1:max(r$stopri[,1])),labels=r$stopri[,1])

#symbolic data from .csv file
#library(clusterSim)
#dsym<-as.matrix(read.csv2(file="csv/symbolic.csv"))
#dim(dsym)<-c(dim(dsym)[1],dim(dsym)[2]/%2,2)
#r<- HINoV.Symbolic(dsym, u=5)
#print(r$stopri)
#plot(r$stopri[,2], xlab="Variable number", ylab="topri",
#xaxt="n", type="b")
#axis(1,at=c(1:max(r$stopri[,1])),labels=r$stopri[,1])
```

---

index.C

*Calculates Hubert & Levin C index - internal cluster quality index*


---

**Description**

Calculates Hubert & Levin C index - internal cluster quality index

**Usage**

```
index.C(d,cl)
```

**Arguments**

d	'dist' object
cl	A vector of integers indicating the cluster to which each object is allocated

**Details**

See file `\\$R\_HOME\library\clusterSim\pdf\indexC\_details.pdf` for further details

Thanks to Özge Sahin from Technical University of Munich for pointing the difference between [index.G3](#) and [index.C](#).

**Value**

calculated C index

**Author(s)**

Marek Walesiak <marek.walesiak@ue.wroc.pl>, Andrzej Dudek <andrzej.dudek@ue.wroc.pl>

Department of Econometrics and Computer Science, University of Economics, Wrocław, Poland  
<http://keii.ue.wroc.pl/clusterSim>

**References**

Hubert, L.J., Levin, J.R. (1976), A General Statistical Framework for Assessing Categorical Clustering in Free Recall, Psychological Bulletin, Vol. 83, No. 6, 1072-1080.

**See Also**

[index.G1](#), [index.G2](#), [index.G3](#), [index.S](#), [index.H](#), [index.KL](#), [index.Gap](#), [index.DB](#)

**Examples**

```
# Example 1
library(clusterSim)
data(data_ratio)
d <- dist.GDM(data_ratio)
c <- pam(d, 5, diss = TRUE)
icq <- index.C(d,c$clustering)
print(icq)

# Example 2
library(clusterSim)
data(data_ordinal)
d <- dist.GDM(data_ordinal, method="GDM2")
# nc - number_of_clusters
min_nc=2
max_nc=6
res <- array(0,c(max_nc-min_nc+1, 2))
res[,1] <- min_nc:max_nc
clusters <- NULL
for (nc in min_nc:max_nc)
{
  hc <- hclust(d, method="complete")
  cl2 <- cutree(hc, k=nc)
  res[nc-min_nc+1,2] <- C <- index.C(d,cl2)
  clusters <- rbind(clusters,cl2)
}
print(paste("min C for", (min_nc:max_nc)[which.min(res[,2])], "clusters=", min(res[,2])))
print("clustering for min C-index")
print(clusters[which.min(res[,2]),])
#write.table(res, file="C_res.csv", sep=";", dec=".", row.names=TRUE, col.names=FALSE)
plot(res, type="p", pch=0, xlab="Number of clusters", ylab="C", xaxt="n")
axis(1, c(min_nc:max_nc))
```

---

index.DB                      *Calculates Davies-Bouldin's index*

---

### Description

Calculates Davies-Bouldin's cluster separation measure

### Usage

```
index.DB(x, c1, d=NULL, centrotypes="centroids", p=2, q=2)
```

### Arguments

x	data
c1	vector of integers indicating the cluster to which each object is allocated
d	optional distance matrix, used for calculations if centrotypes="medoids"
centrotypes	"centroids" or "medoids"
p	the power of the Minkowski distance between centroids or medoids of clusters: p=1 - Manhattan distance; p=2 - Euclidean distance
q	the power of dispersion measure of a cluster: q=1 - the average distance of objects in the r-th cluster to the centroid or medoid of the r-th cluster; q=2 - the standard deviation of the distance of objects in the r-th cluster to the centroid or medoid of the r-th cluster

### Details

See file [../doc/indexDB\\_details.pdf](#) for further details

Thanks to prof. Christian Hennig <c.hennig@ucl.ac.uk> for finding and fixing the "immutable p" error

### Value

DB	Davies-Bouldin's index
r	vector of maximal R values for each cluster
R	R matrix $(S_r + S_s) / d_{rs}$
d	matrix of distances between centroids or medoids of clusters
S	vector of dispersion measures for each cluster
centers	coordinates of centroids or medoids for all clusters

### Author(s)

Marek Walesiak <marek.walesiak@ue.wroc.pl>, Andrzej Dudek <andrzej.dudek@ue.wroc.pl>  
Department of Econometrics and Computer Science, University of Economics, Wroclaw, Poland  
<http://keii.ue.wroc.pl/clusterSim>



## References

Davies, D.L., Bouldin, D.W. (1979), *A cluster separation measure*, IEEE Transactions on Pattern Analysis and Machine Intelligence, vol. 1, no. 2, 224-227. Available at: <http://dx.doi.org/10.1109/TPAMI.1979.4766909>.

## See Also

[index.G1](#), [index.G2](#), [index.G3](#), [index.C](#), [index.S](#), [index.H](#), [index.Gap](#), [index.KL](#)

## Examples

```
# Example 1
library(clusterSim)
data(data_ratio)
cl1 <- pam(data_ratio, 4)
d<-dist(data_ratio)
print(index.DB(data_ratio, cl1$clustering,d, centrotypes="medoids"))

# Example 2
library(clusterSim)
data(data_ratio)
cl2 <- pam(data_ratio, 5)
print(index.DB(data_ratio, cl2$clustering, centrotypes="centroids"))

# Example 3
library(clusterSim)
data(data_ratio)
md <- dist(data_ratio, method="euclidean")
# nc - number_of_clusters
min_nc=2
max_nc=8
res <- array(0, c(max_nc-min_nc+1, 2))
res[,1] <- min_nc:max_nc
clusters <- NULL
for (nc in min_nc:max_nc)
{
  hc <- hclust(md, method="complete")
  cl2 <- cutree(hc, k=nc)
  res[nc-min_nc+1, 2] <- DB <- index.DB(data_ratio, cl2, centrotypes="centroids")$DB
  clusters <- rbind(clusters, cl2)
}
print(paste("min DB for", (min_nc:max_nc)[which.min(res[,2])], "clusters=", min(res[,2])))
print("clustering for min DB")
print(clusters[which.min(res[,2]),])
#write.table(res, file="DB_res.csv", sep=";", dec=".", row.names=TRUE, col.names=FALSE)
plot(res, type="p", pch=0, xlab="Number of clusters", ylab="DB", xaxt="n")
axis(1, c(min_nc:max_nc))

# Example 4
library(clusterSim)
data(data_ordinal)
md <- dist.GDM(data_ordinal, method="GDM2")
```

```

# nc - number_of_clusters
min_nc=2
max_nc=6
res <- array(0, c(max_nc-min_nc+1, 2))
res[,1] <- min_nc:max_nc
clusters <- NULL
for (nc in min_nc:max_nc)
{
hc <- hclust(md, method="complete")
c12 <- cutree(hc, k=nc)
res[nc-min_nc+1,2] <- DB <- index.DB(data_ordinal, c12, d=md, centrotypes="medoids")$DB
clusters <- rbind(clusters, c12)
}
print(paste("min DB for", (min_nc:max_nc)[which.min(res[,2])], "clusters=", min(res[,2])))
print("clustering for min DB")
print(clusters[which.min(res[,2]),])
#write.table(res, file="DB_res.csv", sep=";", dec=".", row.names=TRUE, col.names=FALSE)
plot(res, type="p", pch=0, xlab="Number of clusters", ylab="DB", xaxt="n")
axis(1, c(min_nc:max_nc))

```

---

index.G1

*Calculates Calinski-Harabasz pseudo F-statistic*


---

## Description

Calculates Calinski-Harabasz pseudo F-statistic

## Usage

```
index.G1 (x, c1, d=NULL, centrotypes="centroids")
```

## Arguments

x	data
c1	A vector of integers indicating the cluster to which each object is allocated
d	optional distance matrix, used for calculations if centrotypes="medoids"
centrotypes	"centroids" or "medoids"

## Details

See file [../doc/indexG1\\_details.pdf](#) for further details.

thank to Nejc Ilc from University of Ljubljana for fixing error for one-element clusters.

## Value

Calinski-Harabasz pseudo F-statistic

**Author(s)**

Marek Walesiak <marek.walesiak@ue.wroc.pl>, Andrzej Dudek <andrzej.dudek@ue.wroc.pl>  
 Department of Econometrics and Computer Science, University of Economics, Wrocław, Poland  
<http://keii.ue.wroc.pl/clusterSim>

**References**

- Calinski, T., Harabasz, J. (1974), *A dendrite method for cluster analysis*, "Communications in Statistics", vol. 3, 1-27. Available at: <http://dx.doi.org/10.1080/03610927408827101>.
- Everitt, B.S., Landau, E., Leese, M. (2001), *Cluster analysis*, Arnold, London, p. 103. ISBN 9780340761199.
- Gatnar, E., Walesiak, M. (Eds.) (2004), *Metody statystycznej analizy wielowymiarowej w badaniach marketingowych [Multivariate statistical analysis methods in marketing research]*, Wydawnictwo AE, Wrocław, p. 338. Available at: [http://keii.ue.wroc.pl/pracownicy/mw/2004\\_Gatnar\\_Walesiak\\_Metody\\_SAW\\_w\\_badaniach\\_marketingowych.pdf](http://keii.ue.wroc.pl/pracownicy/mw/2004_Gatnar_Walesiak_Metody_SAW_w_badaniach_marketingowych.pdf).
- Gordon, A.D. (1999), *Classification*, Chapman & Hall/CRC, London, p. 62. ISBN 9781584880134.
- Milligan, G.W., Cooper, M.C. (1985), *An examination of procedures of determining the number of cluster in a data set*, "Psychometrika", vol. 50, no. 2, 159-179. Available at: <https://dx.doi.org/10.1007/BF02294245>.

**See Also**

[index.G2](#), [index.G3](#), [index.S](#), [index.C](#), [index.H](#), [index.KL](#), [index.Gap](#), [index.DB](#)

**Examples**

```
# Example 1
library(clusterSim)
data(data_ratio)
c<- pam(data_ratio,10)
index.G1(data_ratio,c$clustering)

# Example 2
library(clusterSim)
data(data_ratio)
md <- dist(data_ratio, method="euclidean")
# nc - number_of_clusters
min_nc=2
max_nc=20
res <- array(0,c(max_nc-min_nc+1,2))
res[,1] <- min_nc:max_nc
clusters <- NULL
for (nc in min_nc:max_nc)
{
  c12 <- pam(md, nc, diss=TRUE)
  res[nc-min_nc+1,2] <- G1 <- index.G1(data_ratio,c12$cluster,centrotypes="centroids")
  clusters <- rbind(clusters, c12$cluster)
}
print(paste("max G1 for", (min_nc:max_nc)[which.max(res[,2])], "clusters=", max(res[,2])))
```

```

print("clustering for max G1")
print(clusters[which.max(res[,2]),])
#write.table(res,file="G1_res.csv",sep=";",dec=" ",row.names=TRUE,col.names=FALSE)
plot(res, type="p", pch=0, xlab="Number of clusters", ylab="G1", xaxt="n")
axis(1, c(min_nc:max_nc))

```

---

index.G2

*Calculates G2 internal cluster quality index*


---

### Description

Calculates G2 internal cluster quality index - Baker & Hubert adaptation of Goodman & Kruskal's Gamma statistic

### Usage

```
index.G2(d, c1)
```

### Arguments

d	'dist' object
c1	A vector of integers indicating the cluster to which each object is allocated

### Details

See file `\$R\HOME\library\clusterSim\pdf\indexG2\_details.pdf` for further details

### Value

calculated G2 index

### Author(s)

Marek Walesiak <marek.walesiak@ue.wroc.pl>, Andrzej Dudek <andrzej.dudek@ue.wroc.pl>

Department of Econometrics and Computer Science, University of Economics, Wroclaw, Poland  
<http://keii.ue.wroc.pl/clusterSim>

### References

Everitt, B.S., Landau, E., Leese, M. (2001), *Cluster analysis*, Arnold, London, p. 104. ISBN 9780340761199.

Gatnar, E., Walesiak, M. (Eds.) (2004), *Metody statystycznej analizy wielowymiarowej w badaniach marketingowych [Multivariate statistical analysis methods in marketing research]*, Wydawnictwo AE, Wroclaw, p. 339. Available at: [http://keii.ue.wroc.pl/pracownicy/mw/2004\\_Gatnar\\_Walesiak\\_Metody\\_SAW\\_w\\_badaniach\\_marketingowych.pdf](http://keii.ue.wroc.pl/pracownicy/mw/2004_Gatnar_Walesiak_Metody_SAW_w_badaniach_marketingowych.pdf).

Gordon, A.D. (1999), *Classification*, Chapman & Hall/CRC, London, p. 62. ISBN 9781584880134.

Hubert, L. (1974), *Approximate evaluation technique for the single-link and complete-link hierarchical clustering procedures*, "Journal of the American Statistical Association", vol. 69, no. 347, 698-704. Available at: <http://dx.doi.org/10.1080/01621459.1974.10480191>.

Milligan, G.W., Cooper, M.C. (1985), *An examination of procedures of determining the number of cluster in a data set*, "Psychometrika", vol. 50, no. 2, 159-179. Available at: <https://dx.doi.org/10.1007/BF02294245>.

### See Also

[index.G1](#), [index.G3](#), [index.S](#), [index.H](#), [index.KL](#), [index.Gap](#), [index.C](#), [index.DB](#)

### Examples

```
# Example 1
library(clusterSim)
data(data_ratio)
d <- dist.GDM(data_ratio)
c <- pam(d, 5, diss = TRUE)
icq <- index.G2(d,c$clustering)
print(icq)

# Example 2
library(clusterSim)
data(data_ordinal)
d <- dist.GDM(data_ordinal, method="GDM2")
# nc - number_of_clusters
min_nc=2
max_nc=6
res <- array(0,c(max_nc-min_nc+1, 2))
res[,1] <- min_nc:max_nc
clusters <- NULL
for (nc in min_nc:max_nc)
{
  cl2 <- pam(d, nc, diss=TRUE)
  res[nc-min_nc+1,2] <- G2 <- index.G2(d,cl2$cluster)
  clusters <- rbind(clusters,cl2$cluster)
}
print(paste("max G2 for", (min_nc:max_nc)[which.max(res[,2])], "clusters=", max(res[,2])))
print("clustering for max G2")
print(clusters[which.max(res[,2]),])
#write.table(res, file="G2_res.csv", sep=";", dec=".", row.names=TRUE, col.names=FALSE)
plot(res, type="p", pch=0, xlab="Number of clusters", ylab="G2", xaxt="n")
axis(1, c(min_nc:max_nc))
```

---

index.G3

*Calculates G3 internal cluster quality index*

---

### Description

Calculates G3 internal cluster quality index

**Usage**

```
index.G3(d, c1)
```

**Arguments**

d	'dist' object
c1	A vector of integers indicating the cluster to which each object is allocated

**Details**

See file `\\$R\HOME\library\clusterSim\pdf\indexG3\_details.pdf` for further details

**Value**

calculated G3 index

**Author(s)**

Marek Walesiak <marek.walesiak@ue.wroc.pl>, Andrzej Dudek <andrzej.dudek@ue.wroc.pl>  
Department of Econometrics and Computer Science, University of Economics, Wrocław, Poland  
<http://keii.ue.wroc.pl/clusterSim>

**References**

Gordon, A.D. (1999), *Classification*, Chapman & Hall/CRC, London, p. 62. ISBN 9781584880134.

**See Also**

[index.G1](#), [index.G2](#), [index.S](#), [index.C](#), [index.H](#), [index.KL](#), [index.Gap](#), [index.DB](#)

**Examples**

```
# Example 1
library(clusterSim)
data(data_ratio)
d <- dist.GDM(data_ratio)
c <- pam(d, 5, diss = TRUE)
icq <- index.G3(d, c$clustering)
print(icq)

# Example 2
library(clusterSim)
data(data_ordinal)
d <- dist.GDM(data_ordinal, method="GDM2")
# nc - number_of_clusters
min_nc=2
max_nc=6
res <- array(0, c(max_nc-min_nc+1, 2))
res[,1] <- min_nc:max_nc
clusters <- NULL
```

```

for (nc in min_nc:max_nc)
{
hc <- hclust(d, method="complete")
cl2 <- cutree(hc, k=nc)
res[nc-min_nc+1,2] <- G3 <- index.G3(d,cl2)
clusters <- rbind(clusters,cl2)
}
print(paste("min G3 for", (min_nc:max_nc)[which.min(res[,2])], "clusters=", min(res[,2])))
print("clustering for min G3")
print(clusters[which.min(res[,2]),])
#write.table(res, file="G3_res.csv", sep=";", dec=".", row.names=TRUE, col.names=FALSE)
plot(res, type="p", pch=0, xlab="Number of clusters", ylab="G3", xaxt="n")
axis(1, c(min_nc:max_nc))

```

---

index.Gap

*Calculates Tibshirani, Walther and Hastie gap index*


---

### Description

Calculates Tibshirani, Walther and Hastie gap index

### Usage

```

index.Gap (x, clall, reference.distribution="unif", B=10,
method="pam", d=NULL, centrotypes="centroids")

```

### Arguments

x	data
clall	Two vectors of integers indicating the cluster to which each object is allocated in partition of n objects into u, and u+1 clusters
reference.distribution	"unif" - generate each reference variable uniformly over the range of the observed values for that variable or "pc" - generate the reference variables from a uniform distribution over a box aligned with the principal components of the data. In detail, if $X = \{x_{ij}\}$ is our $n \times m$ data matrix, assume that the columns have mean 0 and compute the singular value decomposition $X = UDV^T$ . We transform via $X' = XV$ and then draw uniform features $Z'$ over the ranges of the columns of $X'$ , as in method a) above. Finally we back-transform via $Z = Z'V^T$ to give reference data $Z$
B	the number of simulations used to compute the gap statistic
method	the cluster analysis method to be used. This should be one of: "ward.D", "ward.D2", "single", "complete", "average", "mcquitty", "median", "centroid", "pam", "k-means", "diana"
d	optional distance matrix, used for calculations if centrotypes="medoids"
centrotypes	"centroids" or "medoids"

**Details**

See file [../doc/indexGap\\_details.pdf](#) for further details

Thanks to dr Michael P. Fay from National Institute of Allergy and Infectious Diseases for finding "one column error".

**Value**

Gap	Tibshirani, Walther and Hastie gap index for u clusters
diffu	necessary value for choosing correct number of clusters via gap statistic $\text{Gap}(u) - [\text{Gap}(u+1) - s(u+1)]$

**Author(s)**

Marek Walesiak <marek.walesiak@ue.wroc.pl>, Andrzej Dudek <andrzej.dudek@ue.wroc.pl>  
 Department of Econometrics and Computer Science, University of Economics, Wroclaw, Poland  
<http://keii.ue.wroc.pl/clusterSim>

**References**

Tibshirani, R., Walther, G., Hastie, T. (2001), *Estimating the number of clusters in a data set via the gap statistic*, "Journal of the Royal Statistical Society", ser. B, vol. 63, part 2, 411-423. Available at: <http://dx.doi.org/10.1111/1467-9868.00293>.

**See Also**

[index.G1](#), [index.G2](#), [index.G3](#), [index.C](#), [index.S](#), [index.H](#), [index.KL](#), [index.DB](#)

**Examples**

```
# Example 1
library(clusterSim)
data(data_ratio)
cl1<-pam(data_ratio,4)
cl2<-pam(data_ratio,5)
clall<-cbind(cl1$clustering,cl2$clustering)
g<-index.Gap(data_ratio, clall, reference.distribution="unif", B=10,
  method="pam")
print(g)

# Example 2
library(clusterSim)
means <- matrix(c(0,2,4,0,3,6), 3, 2)
cov <- matrix(c(1,-0.9,-0.9,1), 2, 2)
x <- cluster.Gen(numObjects=40, means=means, cov=cov, model=2)
x <- x$data
md <- dist(x, method="euclidean")^2
# nc - number_of_clusters
min_nc=1
max_nc=5
min <- 0
```



```

clopt <- NULL
res <- array(0, c(max_nc-min_nc+1, 2))
res[,1] <- min_nc:max_nc
found <- FALSE
for (nc in min_nc:max_nc){
  cl1 <- pam(md, nc, diss=TRUE)
  cl2 <- pam(md, nc+1, diss=TRUE)
  clall <- cbind(cl1$clustering, cl2$clustering)
  gap <- index.Gap(x,clall,B=20,method="pam",centrotypes="centroids")
  res[nc-min_nc+1, 2] <- diffu <- gap$diffu
  if ((res[nc-min_nc+1, 2] >=0) && (!found)){
    nc1 <- nc
    min <- diffu
    clopt <- cl1$cluster
    found <- TRUE
  }
}
if (found){
print(paste("Minimal nc where diffu>=0 is",nc1,"for diffu=",round(min,4)),quote=FALSE)
}else{
print("I have not found clustering with diffu>=0", quote=FALSE)
}
plot(res,type="p",pch=0,xlab="Number of clusters",ylab="diffu",xaxt="n")
abline(h=0, untf=FALSE)
axis(1, c(min_nc:max_nc))

# Example 3
library(clusterSim)
means <- matrix(c(0,2,4,0,3,6), 3, 2)
cov <- matrix(c(1,-0.9,-0.9,1), 2, 2)
x <- cluster.Gen(numObjects=40, means=means, cov=cov, model=2)
x <- x$data
md <- dist(x, method="euclidean")^2
# nc - number_of_clusters
min_nc=1
max_nc=5
min <- 0
clopt <- NULL
res <- array(0, c(max_nc-min_nc+1, 2))
res[,1] <- min_nc:max_nc
found <- FALSE
for (nc in min_nc:max_nc){
  cl1 <- pam(md, nc, diss=TRUE)
  cl2 <- pam(md, nc+1, diss=TRUE)
  clall <- cbind(cl1$clustering, cl2$clustering)
  gap <- index.Gap(x,clall,B=20,method="pam",d=md,centrotypes="medoids")
  res[nc-min_nc+1, 2] <- diffu <- gap$diffu
  if ((res[nc-min_nc+1, 2] >=0) && (!found)){
    nc1 <- nc
    min <- diffu
    clopt <- cl1$cluster
    found <- TRUE
  }
}

```

```
}
if (found){
print(paste("Minimal nc where diffu>=0 is",nc1,"for diffu=",round(min,4)),quote=FALSE)
}else{
print("I have not found clustering with diffu>=0",quote=FALSE)
}
plot(res, type="p", pch=0, xlab="Number of clusters", ylab="diffu", xaxt="n")
abline(h=0, untf=FALSE)
axis(1, c(min_nc:max_nc))
```

---

index.H

*Calculates Hartigan index*

---

### Description

Calculates Hartigan index

### Usage

```
index.H (x,clall,d=NULL,centrotypes="centroids")
```

### Arguments

x	data
clall	Two vectors of integers indicating the cluster to which each object is allocated in partition of n objects into u and u+1 clusters
d	optional distance matrix, used for calculations if centrotypes="medoids"
centrotypes	"centroids" or "medoids"

### Details

See file `\\$R_HOME\library\clusterSim\pdf\indexH_details.pdf` for further details

### Value

Hartigan index

### Author(s)

Marek Walesiak <marek.walesiak@ue.wroc.pl>, Andrzej Dudek <andrzej.dudek@ue.wroc.pl>  
Department of Econometrics and Computer Science, University of Economics, Wroclaw, Poland  
<http://keii.ue.wroc.pl/clusterSim>

## References

- Hartigan, J. (1975), *Clustering algorithms*, Wiley, New York. ISBN 047135645X.
- Milligan, G.W., Cooper, M.C. (1985), *An examination of procedures of determining the number of cluster in a data set*, "Psychometrika", vol. 50, no. 2, 159-179. Available at: <https://dx.doi.org/10.1007/BF02294245>.
- Tibshirani, R., Walther, G., Hastie, T. (2001), *Estimating the number of clusters in a data set via the gap statistic*, "Journal of the Royal Statistical Society", ser. B, vol. 63, part 2, 411-423. Available at: <http://dx.doi.org/10.1111/1467-9868.00293>.

## See Also

[index.G1](#), [index.G2](#), [index.G3](#), [index.C](#), [index.S](#), [index.KL](#), [index.Gap](#), [index.DB](#)

## Examples

```
# Example 1
library(clusterSim)
data(data_ratio)
cl1<-pam(data_ratio,4)
cl2<-pam(data_ratio,5)
clall<-cbind(cl1$clustering,cl2$clustering)
index.H(data_ratio,clall)

# Example 2
library(clusterSim)
data(data_ratio)
md <- dist(data_ratio, method="euclidean")
# nc - number_of_clusters
min_nc=1
max_nc=20
min <- 0
res <- array(0, c(max_nc-min_nc+1, 2))
res[,1] <- min_nc:max_nc
found <- FALSE
clusters <- NULL
for (nc in min_nc:max_nc)
{
  print(nc)
  hc <- hclust(md, method="complete")
  cl1 <- cutree(hc, k=nc)
  cl2 <- cutree(hc, k=nc+1)
  clall <- cbind(cl1,cl2)
  res[nc-min_nc+1,2] <- H <- index.H(data_ratio,clall,centrotypes="centroids")
  if ((res[nc-min_nc+1, 2]<10) && (!found)){
    nc1 <- nc
    min <- H
    clopt <- cl1
    found <- TRUE
  }
}
if (found)
```

```

{
print(paste("minimal nc for H<=10 equals",nc1,"for H=",min))
print("clustering for minimal nc where H<=10")
print(clopt)
}else
{
print("Clustering not found with H<=10")
}
}
#write.table(res,file="H_res.csv",sep=";",dec="," ,row.names=TRUE,col.names=FALSE)
plot(res,type="p",pch=0,xlab="Number of clusters",ylab="H",xaxt="n")
abline(h=10, untf=FALSE)
axis(1, c(min_nc:max_nc))

# Example 3
library(clusterSim)
data(data_ratio)
md <- dist(data_ratio, method="manhattan")
# nc - number_of_clusters
min_nc=1
max_nc=20
min <- 0
res <- array(0, c(max_nc-min_nc+1, 2))
res[,1] <- min_nc:max_nc
found <- FALSE
clusters <- NULL
for (nc in min_nc:max_nc)
{
print(nc)
hc <- hclust(md, method="complete")
cl1 <- cutree(hc, k=nc)
cl2 <- cutree(hc, k=nc+1)
clall <- cbind(cl1,cl2)
res[nc-min_nc+1,2] <- H <- index.H(data_ratio,clall,d=md,centrotypes="medoids")
if ((res[nc-min_nc+1, 2]<10) && (!found)){
nc1 <- nc
min <- H
clopt <- cl1
found <- TRUE
}
}
}
if (found)
{
print(paste("minimal nc for H<=10 equals",nc1,"for H=",min))
print("clustering for minimal nc where H<=10")
print(clopt)
}else
{
print("Clustering not found with H<=10")
}
}
#write.table(res,file="H_res.csv",sep=";",dec="," ,row.names=TRUE,col.names=FALSE)
plot(res,type="p",pch=0,xlab="Number of clusters",ylab="H",xaxt="n")
abline(h=10, untf=FALSE)
axis(1, c(min_nc:max_nc))

```

---

index.KL	<i>Calculates Krzanowski-Lai index</i>
----------	--

---

**Description**

Calculates Krzanowski-Lai index

**Usage**

```
index.KL (x,clall,d=NULL,centrotypes="centroids")
```

**Arguments**

x	data
clall	Three vectors of integers indicating the cluster to which each object is allocated in partition of n objects into u-1, u, and u+1 clusters
d	optional distance matrix, used for calculations if centrotypes="medoids"
centrotypes	"centroids" or "medoids"

**Details**

See file [../doc/indexKL\\_details.pdf](#) for further details

**Value**

Krzanowski-Lai index

**Author(s)**

Marek Walesiak <marek.walesiak@ue.wroc.pl>, Andrzej Dudek <andrzej.dudek@ue.wroc.pl>  
Department of Econometrics and Computer Science, University of Economics, Wroclaw, Poland  
<http://keii.ue.wroc.pl/clusterSim>

**References**

Krzanowski, W.J., Lai, Y.T. (1988), *A criterion for determining the number of groups in a data set using sum of squares clustering*, "Biometrics", 44, 23-34.

Milligan, G.W., Cooper, M.C. (1985), *An examination of procedures of determining the number of cluster in a data set*, "Psychometrika", vol. 50, no. 2, 159-179. Available at: <https://dx.doi.org/10.1007/BF02294245>.

Tibshirani, R., Walther, G., Hastie, T. (2001), *Estimating the number of clusters in a data set via the gap statistic*, "Journal of the Royal Statistical Society", ser. B, vol. 63, part 2, 411-423. Available at: <http://dx.doi.org/10.1111/1467-9868.00293>.

**See Also**

[index.G1](#), [index.G2](#), [index.G3](#), [index.C](#), [index.S](#), [index.H](#), [index.Gap](#), [index.DB](#)

**Examples**

```

# Example 1
library(clusterSim)
data(data_ratio)
cl1<-pam(data_ratio,4)
cl2<-pam(data_ratio,5)
cl3<-pam(data_ratio,6)
clall<-cbind(cl1$clustering,cl2$clustering,cl3$clustering)
index.KL(data_ratio,clall)

# Example 2
library(clusterSim)
data(data_ratio)
md <- dist(data_ratio, method="manhattan")
# nc - number_of_clusters
min_nc=2
max_nc=15
res <- array(0, c(max_nc-min_nc+1, 2))
res[,1] <- min_nc:max_nc
clusters <- NULL
for (nc in min_nc:max_nc)
{
  if(nc-1==1){
    clustering1<-rep(1,nrow(data_ratio))
  }
  else{
    clustering1 <- pam(md, nc-1, diss=TRUE)$clustering
  }
  clustering2 <- pam(md, nc, diss=TRUE)$clustering
  clustering3 <- pam(md, nc+1, diss=TRUE)$clustering
  clall<- cbind(clustering1, clustering2, clustering3)
  res[nc-min_nc+1,2] <- KL <- index.KL(data_ratio,clall,centrotypes="centroids")
  clusters <- rbind(clusters, clustering2)
}
print(paste("max KL for", (min_nc:max_nc)[which.max(res[,2])], "clusters=", max(res[,2])))
print("clustering for max KL")
print(clusters[which.max(res[,2]),])
#write.table(res,file="KL_res.csv", sep=";", dec=".", row.names=TRUE, col.names=FALSE)
plot(res,type="p",pch=0,xlab="Number of clusters",ylab="KL",xaxt="n")
axis(1, c(min_nc:max_nc))

# Example 3
library(clusterSim)
data(data_ratio)
md <- dist(data_ratio, method="manhattan")
# nc - number_of_clusters
min_nc=2
max_nc=15
res <- array(0, c(max_nc-min_nc+1, 2))
res[,1] <- min_nc:max_nc
clusters <- NULL
for (nc in min_nc:max_nc)

```

```

{
  if(nc-1==1){
    clustering1<-rep(1,nrow(data_ratio))
  }
  else{
    clustering1 <- pam(md, nc-1, diss=TRUE)$clustering
  }
  clustering2 <- pam(md, nc, diss=TRUE)$clustering
  clustering3 <- pam(md, nc+1, diss=TRUE)$clustering
  clall<- cbind(clustering1, clustering2, clustering3)
  res[nc-min_nc+1,2] <- KL <- index.KL(data_ratio,clall,d=md,centrotypes="medoids")
  clusters <- rbind(clusters, clustering2)
}
print(paste("max KL for", (min_nc:max_nc)[which.max(res[,2])], "clusters=", max(res[,2])))
print("clustering for max KL")
print(clusters[which.max(res[,2]),])
#write.table(res,file="KL_res.csv",sep=";",dec="," ,row.names=TRUE,col.names=FALSE)
plot(res,type="p",pch=0,xlab="Number of clusters",ylab="KL",xaxt="n")
axis(1, c(min_nc:max_nc))

```

---

index.S

*Calculates Rousseeuw's Silhouette internal cluster quality index*


---

### Description

Calculates Rousseeuw's Silhouette internal cluster quality index

### Usage

```
index.S(d,cl,singleObject=0)
```

### Arguments

d	'dist' object
cl	A vector of integers indicating the cluster to which each object is allocated
singleObject	0 - $s(i)=0$ or 1 - $s(i)=1$ . When cluster contains a single object, it is unclear how $a(i)$ of Silhouette index should be defined (see Kaufman & Rousseeuw (1990), p. 85).

### Details

See file `\\$R_HOME\library\clusterSim\pdf\indexS\_details.pdf` for further details

### Value

calculated Silhouette index

**Author(s)**

Marek Walesiak <marek.walesiak@ue.wroc.pl>, Andrzej Dudek <andrzej.dudek@ue.wroc.pl>  
 Department of Econometrics and Computer Science, University of Economics, Wrocław, Poland  
<http://keii.ue.wroc.pl/clusterSim>

**References**

Gatnar, E., Walesiak, M. (Eds.) (2004), *Metody statystycznej analizy wielowymiarowej w badaniach marketingowych [Multivariate statistical analysis methods in marketing research]*, Wydawnictwo AE, Wrocław, 342-343, erratum. Available at: [http://keii.ue.wroc.pl/pracownicy/mw/2004\\_Gatnar\\_Walesiak\\_Metody\\_SAW\\_w\\_badaniach\\_marketingowych.pdf](http://keii.ue.wroc.pl/pracownicy/mw/2004_Gatnar_Walesiak_Metody_SAW_w_badaniach_marketingowych.pdf).

Kaufman, L., Rousseeuw, P.J. (1990), *Finding groups in data: an introduction to cluster analysis*, Wiley, New York, pp. 83-88. ISBN: 978-0-471-73578-6.

**See Also**

[index.G1](#), [index.G2](#), [index.G3](#), [index.C](#), [index.KL](#), [index.H](#), [index.Gap](#), [index.DB](#)

**Examples**

```
# Example 1
library(clusterSim)
data(data_ratio)
d <- dist.GDM(data_ratio)
c <- pam(d, 5, diss = TRUE)
icq <- index.S(d,c$clustering)
print(icq)

# Example 2
library(clusterSim)
data(data_ratio)
md <- dist(data_ratio, method="manhattan")
# nc - number_of_clusters
min_nc=2
max_nc=20
res <- array(0, c(max_nc-min_nc+1, 2))
res[,1] <- min_nc:max_nc
clusters <- NULL
for (nc in min_nc:max_nc)
{
  cl2 <- pam(md, nc, diss=TRUE)
  res[nc-min_nc+1, 2] <- S <- index.S(md,cl2$cluster)
  clusters <- rbind(clusters, cl2$cluster)
}
print(paste("max S for", (min_nc:max_nc)[which.max(res[,2])], "clusters=", max(res[,2])))
print("clustering for max S")
print(clusters[which.max(res[,2]),])
#write.table(res, file="S_res.csv", sep=";", dec=".", row.names=TRUE, col.names=FALSE)
plot(res, type="p", pch=0, xlab="Number of clusters", ylab="S", xaxt="n")
axis(1, c(min_nc:max_nc))
```



---

`initial.Centers`*Calculation of initial clusters centers for k-means like algorithms*

---

**Description**

Function calculates initial clusters centers for k-means like algorithms with the following algorithm (similar to SPSS QuickCluster function)

(a) if the distance between  $x_k$  and its closest cluster center is greater than the distance between the two closest centers ( $M_m$  and  $M_n$ ), then  $x_k$  replaces either  $M_m$  or  $M_n$ , whichever is closer to  $x_k$ .

(b) If  $x_k$  does not replace a cluster initial center in (a), a second test is made: If that distance  $d_q$  greater than the distance between  $M_q$  and its closest  $M_i$ , then  $x_k$  replaces  $M_q$ .

where:

$M_i$  - initial center of  $i$ -th cluster

$x_k$  - vector of  $k$ -th observation

$d(\dots, \dots)$  - Euclidean distance

$d_{mn} = \min_{ij} d(M_i, M_j)$

$d_q = \min_i d(x_k, M_i)$

**Usage**

```
initial.Centers(x, k)
```

**Arguments**

x	matrix or dataset
k	number of initial cluster centers

**Value**

Numbers of objects chosen as initial cluster centers

**Author(s)**

Marek Walesiak <marek.walesiak@ue.wroc.pl>, Andrzej Dudek <andrzej.dudek@ue.wroc.pl>  
Department of Econometrics and Computer Science, University of Economics, Wroclaw, Poland  
<http://keii.ue.wroc.pl/clusterSim>

**References**

Hartigan, J. (1975), *Clustering algorithms*, Wiley, New York. ISBN 0-471-35645-X.

**See Also**

[cluster.Sim](#)

**Examples**

```
#Example 1 (numbers of objects choosen as initial cluster centers)
library(clusterSim)
data(data_ratio)
ic <- initial.Centers(data_ratio, 10)
print(ic)

#Example 2 (application with kmeans algorithm)
library(clusterSim)
data(data_ratio)
kmeans(data_ratio,data_ratio[initial.Centers(data_ratio, 10),])
```

---

interval\_normalization

*Types of normalization formulas for interval-valued symbolic variables*

---

**Description**

Types of normalization formulas for interval-valued symbolic variables

**Usage**

```
interval_normalization(x,dataType="simple", type="n0",y=NULL,...)
```

**Arguments**

x	matrix dataset or symbolic table object
dataType	Type of symbolic data table passed to function, 'sda' - full symbolicDA format object; 'simple' - three dimensional array with lower and upper bound of intervals in third dimension; 'separate_tables' - lower bounds of intervals in x, upper bounds in y; 'rows' - lower and upper bound of intervals in neighbouring rows; 'columns' - lower and upper bound of intervals in neighbouring columns
type	type of normalization: n0 - without normalization n1 - standardization $((x-\text{mean})/\text{sd})$ n2 - positional standardization $((x-\text{median})/\text{mad})$ n3 - unitization $((x-\text{mean})/\text{range})$ n3a - positional unitization $((x-\text{median})/\text{range})$ n4 - unitization with zero minimum $((x-\text{min})/\text{range})$ n5 - normalization in range $\langle -1,1 \rangle ((x-\text{mean})/\max(\text{abs}(x-\text{mean})))$ n5a - positional normalization in range $\langle -1,1 \rangle ((x-\text{median})/\max(\text{abs}(x-\text{median})))$ n6 - quotient transformation $(x/\text{sd})$

n6a - positional quotient transformation ( $x/\text{mad}$ )  
n7 - quotient transformation ( $x/\text{range}$ )  
n8 - quotient transformation ( $x/\text{max}$ )  
n9 - quotient transformation ( $x/\text{mean}$ )  
n9a - positional quotient transformation ( $x/\text{median}$ )  
n10 - quotient transformation ( $x/\text{sum}$ )  
n11 - quotient transformation ( $x/\text{sqrt}(\text{SSQ})$ )  
n12 - normalization ( $(x-\text{mean})/\text{sqrt}(\text{sum}((x-\text{mean})^2))$ )  
n12a - positional normalization ( $(x-\text{median})/\text{sqrt}(\text{sum}((x-\text{median})^2))$ )  
n13 - normalization with zero being the central point ( $(x-\text{midrange})/(\text{range}/2)$ )  
y matrix or dataset with upper bounds of intervals if argument `dataType` is `uuqal` to `"separate_tables"`  
... arguments passed to `sum`, `mean`, `min`, `sd`, `mad` and other aggregation functions. In particular: `na.rm` - a logical value indicating whether NA values should be stripped before the computation

**Value**

Normalized data

**Author(s)**

Marek Walesiak <marek.walesiak@ue.wroc.pl>, Andrzej Dudek <andrzej.dudek@ue.wroc.pl>  
Department of Econometrics and Computer Science, University of Economics, Wrocław, Poland  
<http://keii.ue.wroc.pl/clusterSim>

**References**

- Jajuga, K., Walesiak, M. (2000), *Standardisation of data set under different measurement scales*, In: R. Decker, W. Gaul (Eds.), *Classification and information processing at the turn of the millennium*, Springer-Verlag, Berlin, Heidelberg, 105-112. Available at: [http://dx.doi.org/10.1007/978-3-642-57280-7\\_11](http://dx.doi.org/10.1007/978-3-642-57280-7_11).
- Milligan, G.W., Cooper, M.C. (1988), *A study of standardization of variables in cluster analysis*, "Journal of Classification", vol. 5, 181-204. Available at: <https://dx.doi.org/10.1007/BF01897163>.
- Walesiak, M. (2014), *Przegląd formuł normalizacji wartości zmiennych oraz ich własności w statystycznej analizie wielowymiarowej [Data normalization in multivariate data analysis. An overview and properties]*, "Przegląd Statystyczny" ("Statistical Review"), vol. 61, no. 4, 363-372. Available at: [http://keii.ue.wroc.pl/pracownicy/mw/2014\\_Walesiak\\_Przegląd\\_Statystyczny\\_z\\_4.pdf](http://keii.ue.wroc.pl/pracownicy/mw/2014_Walesiak_Przegląd_Statystyczny_z_4.pdf).
- Walesiak, M., Dudek, A. (2017), *Selecting the Optimal Multidimensional Scaling Procedure for Metric Data with R Environment*, „STATISTICS IN TRANSITION new series”, September, Vol. 18, No. 3, pp. 521-540. Available at: <http://stat.gov.pl/en/sit-en/issues-and-articles-sit/>.

**See Also**

[data.Normalization](#)

**Examples**

```
library(clusterSim)
data(data_symbolic_interval_polish_voivodships)
n<-interval_normalization(data_symbolic_interval_polish_voivodships,dataType="simple",type="n2")
plotInterval(n$simple)
```

---

ordinalToMetric	<i>Reinforcing measurement scale for ordinal data</i>
-----------------	---

---

**Description**

Reinforcing measurement scale for ordinal data (ordinal to metric scale)

**Usage**

```
ordinalToMetric(data,scaleType="o",patternCoordinates)
```

**Arguments**

data	matrix or dataset
scaleType	"o" - variables measured on ordinal scale, "m" - variables measured on metric scale, "o/m" - vector with mixed variables - e.g. c("o","m","m","o","o","m")
patternCoordinates	vector containing pattern coordinates c(...) given by the reaseracher for data (for metric variables - NA, for ordinal variables - one of the categories for each ordinal variable (e.g. maximum category))

**Details**

See file [../doc/ordinalToMetric\\_details.pdf](#) for further details

**Value**

pdata	raw (primary) data matrix
tdata	data matrix after transformation of ordinal variables into metric variables
cpattern	vector containing pattern coordinates

**Author(s)**

Marek Walesiak <marek.walesiak@ue.wroc.pl>, Andrzej Dudek <andrzej.dudek@ue.wroc.pl>  
 Department of Econometrics and Computer Science, Wroclaw University of Economics, Poland  
<http://keii.ue.wroc.pl/clusterSim>

## References

Jajuga, K., Walesiak, M., Bak, A. (2003), *On the general distance measure*, In: M. Schwaiger, O. Opitz (Eds.), *Exploratory data analysis in empirical research*, Springer-Verlag, Berlin, Heidelberg, 104-109. Available at: [http://dx.doi.org/10.1007/978-3-642-55721-7\\_12](http://dx.doi.org/10.1007/978-3-642-55721-7_12).

Walesiak, M. (1993), *Statystyczna analiza wielowymiarowa w badaniach marketingowych [Multivariate statistical analysis in marketing research]*. Wrocław University of Economics, Research Papers no. 654. Available at: [http://keii.ue.wroc.pl/pracownicy/mw/1993\\_Walesiak\\_SAW\\_w\\_badaniach\\_marketingowych\\_OCR.pdf](http://keii.ue.wroc.pl/pracownicy/mw/1993_Walesiak_SAW_w_badaniach_marketingowych_OCR.pdf).

Walesiak, M. (1999), *Distance Measure for Ordinal Data*, "Argumenta Oeconomica", No. 2 (8), 167-173. Available at: [http://keii.ue.wroc.pl/pracownicy/mw/1999\\_Walesiak\\_Argumenta\\_Oeconomica\\_no\\_2.pdf](http://keii.ue.wroc.pl/pracownicy/mw/1999_Walesiak_Argumenta_Oeconomica_no_2.pdf).

Walesiak, M. (2011), *Uogólniona miara odległości GDM w statystycznej analizie wielowymiarowej z wykorzystaniem programu R [The Generalized Distance Measure GDM in multivariate statistical analysis with R]*, Wydawnictwo Uniwersytetu Ekonomicznego, Wrocław. Available at: [http://keii.ue.wroc.pl/pracownicy/mw/2011\\_Walesiak\\_Uogolniona\\_miara\\_odleglosci\\_GDM\\_w\\_SAW\\_z\\_wykorzystaniem\\_programu\\_R\\_errata.pdf](http://keii.ue.wroc.pl/pracownicy/mw/2011_Walesiak_Uogolniona_miara_odleglosci_GDM_w_SAW_z_wykorzystaniem_programu_R_errata.pdf).

Walesiak, M. (2014), *Wzmacnianie skali pomiaru dla danych porządkowych w statystycznej analizie wielowymiarowej [Reinforcing measurement scale for ordinal data in multivariate statistical analysis]*, Taksonomia 22, Prace Naukowe Uniwersytetu Ekonomicznego we Wrocławiu no. 327, 60-68. Available at: [http://keii.ue.wroc.pl/pracownicy/mw/2014\\_Walesiak\\_Taksonomia\\_22\\_PN\\_UE\\_327.pdf](http://keii.ue.wroc.pl/pracownicy/mw/2014_Walesiak_Taksonomia_22_PN_UE_327.pdf).

## See Also

[dist.GDM](#)

## Examples

```
# Example 1
library(clusterSim)
data(data_patternGDM2)
res1<-ordinalToMetric(data_patternGDM2, scaleType="o", patternCoordinates=c(5,4,3,1,1,3))
print(res1)
```

```
# Example 2
library(clusterSim)
data(data_patternGDM2)
res2<-ordinalToMetric(data_patternGDM2, scaleType="o", patternCoordinates=c(5,4,3,4,2,4))
print(res2)
```

**Description**

An application of GDM1 distance for metric data to compute the distances of objects from the upper (ideal point co-ordinates) or lower (anti-ideal point co-ordinates) pattern object

**Usage**

```
pattern.GDM1(data, performanceVariable, scaleType="i",
nomOptValues=NULL, weightsType="equal", weights=NULL,
normalization="n0", patternType="upper",
patternCoordinates="dataBounds", patternManual=NULL,
nominalTransfMethod=NULL)
```

**Arguments**

data	matrix or dataset
performanceVariable	vector containing three types of performance variables: s for stimulants where higher value means better performance d for destimulants where low values indicate better performance n for nominants where the best value is implied. Object performance is positively assessed if the measure has implied value
scaleType	"i" - variables measured on interval scale, "r" - variables measured on ratio scale, "r/i" - vector with mixed variables
nomOptValues	vector containing optimal values for nominant variables and NA values for stimulants and destimulants. If performanceVariable do not contain nominant variables this nomOptValues may be set to NULL
weightsType	equal or different1 or different2 "equal" - equal weights "different1" - vector of different weights should satisfy conditions: each weight takes value from interval [0; 1] and sum of weights equals one "different2" - vector of different weights should satisfy conditions: each weight takes value from interval [0; m] and sum of weights equals m (m - the number of variables)
normalization	normalization formulas as in data.Normalization function
weights	vector of weights
patternType	"upper" - ideal point co-ordinates consists of the best variables' values "lower" - anti-ideal point co-ordinates consists of the worst variables' values
patternCoordinates	"dataBounds" - pattern should be calculated as following: "upper" pattern (maximum for stimulants, minimum for destimulants), "lower" pattern (minimum for stimulants, maximum for destimulants) "manual" - pattern should be given in patternManual variable
patternManual	Pattern co-ordinates contain: real numbers "min" - for minimal value of variable "max" - for maximal value of variable

nominalTransfMethod

method of transformation of nominant to stimulant variable:

"q" - quotient transformation

"d" - difference transformation

## Details

See file [../doc/patternGDM1\\_details.pdf](#) for further details

## Value

pdata	raw (primary) data matrix
tdata	data matrix after transformation of nominant variables (with pattern in last row)
data	data matrix after normalization (with pattern in last row)
distances	GDM1 distances from pattern object
sortedDistances	sorted GDM1 distances from pattern object

## Author(s)

Marek Walesiak <[marek.walesiak@ue.wroc.pl](mailto:marek.walesiak@ue.wroc.pl)>, Andrzej Dudek <[andrzej.dudek@ue.wroc.pl](mailto:andrzej.dudek@ue.wroc.pl)>  
 Department of Econometrics and Computer Science, University of Economics, Wrocław, Poland  
<http://keii.ue.wroc.pl/clusterSim>

## References

- Jajuga, K., Walesiak, M., Bak, A. (2003), *On the general distance measure*, In: M. Schwaiger, O. Opitz (Eds.), *Exploratory data analysis in empirical research*, Springer-Verlag, Berlin, Heidelberg, 104-109. Available at: [http://dx.doi.org/10.1007/978-3-642-55721-7\\_12](http://dx.doi.org/10.1007/978-3-642-55721-7_12).
- Walesiak, M. (1993), *Statystyczna analiza wielowymiarowa w badaniach marketingowych [Multivariate statistical analysis in marketing research]*. Wrocław University of Economics, Research Papers no. 654. Available at: [http://keii.ue.wroc.pl/pracownicy/mw/1993\\_Walesiak\\_SAW\\_w\\_badaniach\\_marketingowych\\_OCR.pdf](http://keii.ue.wroc.pl/pracownicy/mw/1993_Walesiak_SAW_w_badaniach_marketingowych_OCR.pdf).
- Walesiak, M. (2006), *Uogólniona miara odległości w statystycznej analizie wielowymiarowej [The Generalized Distance Measure in multivariate statistical analysis]*, Wydawnictwo AE, Wrocław. Available at: [http://keii.ue.wroc.pl/pracownicy/mw/2006\\_Walesiak\\_Uogolniona\\_miara\\_odleglosci.pdf](http://keii.ue.wroc.pl/pracownicy/mw/2006_Walesiak_Uogolniona_miara_odleglosci.pdf).
- Walesiak, M. (2011), *Uogólniona miara odległości GDM w statystycznej analizie wielowymiarowej z wykorzystaniem programu R [The Generalized Distance Measure GDM in multivariate statistical analysis with R]*, Wydawnictwo Uniwersytetu Ekonomicznego, Wrocław. Available at: [http://keii.ue.wroc.pl/pracownicy/mw/2011\\_Walesiak\\_Uogolniona\\_miara\\_odleglosci\\_GDM\\_w\\_SAW\\_z\\_wykorzystaniem\\_programu\\_R\\_errata.pdf](http://keii.ue.wroc.pl/pracownicy/mw/2011_Walesiak_Uogolniona_miara_odleglosci_GDM_w_SAW_z_wykorzystaniem_programu_R_errata.pdf).
- Walesiak, M. (2016), *Uogólniona miara odległości GDM w statystycznej analizie wielowymiarowej z wykorzystaniem programu R. Wydanie 2 poprawione i rozszerzone [The Generalized Distance Measure GDM in multivariate statistical analysis with R]*, Wydawnictwo Uniwersytetu Ekonomicznego, Wrocław. Available at: [http://keii.ue.wroc.pl/pracownicy/mw/2016\\_Walesiak\\_Uogolniona\\_miara\\_odleglosci\\_GDM.pdf](http://keii.ue.wroc.pl/pracownicy/mw/2016_Walesiak_Uogolniona_miara_odleglosci_GDM.pdf).

**See Also**

[dist.GDM,data.Normalization](#)

**Examples**

```
# Example 1
library(clusterSim)
data(data_patternGDM1)
res<-pattern.GDM1(data_patternGDM1,
performanceVariable=c("s","s","s","s","s","s","d","d","s","s"),
scaleType="r",nomOptValues=NULL,weightsType<-"equal",weights=NULL,
normalization<-"n4",patternType<-"lower",patternCoordinates<-"manual",
patternManual<-c("min","min","min","min","min","min","max","max","min","min"),
nominalTransfMethod <-NULL)
print(res)
gdm_p<-res$distances
plot(cbind(gdm_p,gdm_p),xlim=c(max(gdm_p),min(gdm_p)),
ylim=c(min(gdm_p),max(gdm_p)),xaxt="n",
xlab="Order of objects from the best to the worst",
ylab="GDM distances from pattern object", lwd=1.6)
axis(1, at=gdm_p,labels=names(gdm_p), cex.axis=0.5)
```

```
# Example 2
library(clusterSim)
data(data_patternGDM1)
res<-pattern.GDM1(data_patternGDM1,
performanceVariable=c("s","s","s","s","s","s","d","d","s","s"),
scaleType="r",nomOptValues=NULL,weightsType<-"equal",weights=NULL,
normalization<-"n2",patternType<-"upper",
patternCoordinates<-"dataBounds",patternManual<-NULL,
nominalTransfMethod<-NULL)
print(res)
gdm_p<-res$distances
plot(cbind(gdm_p,gdm_p),xlim=c(min(gdm_p),max(gdm_p)),
ylim=c(min(gdm_p),max(gdm_p)),xaxt="n",
xlab="Order of objects from the best to the worst",
ylab="GDM distances from pattern object", lwd=1.6)
axis(1, at=gdm_p,labels=names(gdm_p), cex.axis=0.5)
```

```
# Example 3
library(clusterSim)
data(data_patternGDM1)
res<-pattern.GDM1(data_patternGDM1,
performanceVariable=c("s","s","s","s","s","s","d","d","s","s"),
scaleType="r",nomOptValues=NULL,weightsType<-"different2",
weights=c(1.1,1.15,1.15,1.1,1.1,0.7,0.7,1.2,0.8,1.0),
normalization<-"n6",patternType<-"upper",patternCoordinates<-"manual",
patternManual<-c(100,100,100,100,100,"max","min","min","max","max"),
nominalTransfMethod <-NULL)
print(res)
gdm_p<-res$distances
plot(cbind(gdm_p,gdm_p),xlim=c(min(gdm_p),max(gdm_p)),
```



```
ylim=c(min(gdm_p),max(gdm_p)),xaxt="n",
xlab="Order of objects from the best to the worst",
ylab="GDM distances from pattern object", lwd=1.6)
axis(1, at=gdm_p,labels=names(gdm_p), cex.axis=0.5)
```

---

pattern.GDM2	<i>An application of GDM2 distance for ordinal data to compute the distances of objects from the pattern object (upper or lower)</i>
--------------	--

---

### Description

An application of GDM2 distance for ordinal data to compute the distances of objects from the upper (ideal point co-ordinates) or lower (anti-ideal point co-ordinates) pattern object

### Usage

```
pattern.GDM2(data, performanceVariable, nomOptValues=NULL,
weightsType="equal", weights=NULL, patternType="upper",
patternCoordinates="dataBounds", patternManual=NULL,
nominalTransfMethod=NULL)
```

### Arguments

data	matrix or dataset
performanceVariable	vector containing three types of performance variables: s for stimulants where higher value means better performance d for destimulants where low values indicate better performance n for nominants where the best value is implied. Object performance is positively assessed if the measure has implied value
nomOptValues	vector containing optimal values for nominant variables and NA values for stimulants and destimulants. If performanceVariable do not contain nominant variables this nomOptValues may be set to NULL
weightsType	equal or different1 or different2 "equal" - equal weights "different1" - vector of different weights should satisfy conditions: each weight takes value from interval [0; 1] and sum of weights equals one "different2" - vector of different weights should satisfy conditions: each weight takes value from interval [0; m] and sum of weights equals m (m - the number of variables)
weights	vector of weights
patternType	"upper" - ideal point co-ordinates consists of the best variables' values "lower" - anti-ideal point co-ordinates consists of the worst variables' values

patternCoordinates	<p>"dataBounds" - pattern should be calculated as following: "upper" pattern (maximum for stimulants, minimum for destimulants, nominal value for nominants), "lower" pattern (minimum for stimulants, maximum for destimulants)</p> <p>"manual" - pattern should be given in patternManual variable</p>
patternManual	<p>Pattern co-ordinates contain:</p> <p>real numbers</p> <p>"min" - for minimal value of variable</p> <p>"max" - for maximal value of variable</p> <p>"nom" - for nominal value of variable (for upper pattern only - given in nomOptValues vector)</p>
nominalTransfMethod	<p>method of transformation of nominant to destimulant variable for patternType="lower":</p> <p>"database" - for each nominant separately GDM2 distance is calculated between each nominant observation (with repetitions - all variable values are used in calculation) and nominal value. Next the variable observations are replaced by those distances</p> <p>"symmetrical" - for each nominant separately GDM2 distance is calculated between each nominant observation (without repetition - each observation is used once) and nominal value. Next the variable observations are replaced by those distances</p>

### Details

See file [../doc/patternGDM2\\_details.pdf](#) for further details

### Value

pdata	raw (primary) data matrix
data	data matrix after transformation of nominant variables (with pattern in last row)
distances	GDM2 distances from pattern object
sortedDistances	sorted GDM2 distances from pattern object

### Author(s)

Marek Walesiak <[marek.walesiak@ue.wroc.pl](mailto:marek.walesiak@ue.wroc.pl)>, Andrzej Dudek <[andrzej.dudek@ue.wroc.pl](mailto:andrzej.dudek@ue.wroc.pl)>  
 Department of Econometrics and Computer Science, University of Economics, Wrocław, Poland  
<http://keii.ue.wroc.pl/clusterSim>

### References

- Jajuga, K., Walesiak, M., Bak, A. (2003), *On the general distance measure*, In: M. Schwaiger, O. Opitz (Eds.), *Exploratory data analysis in empirical research*, Springer-Verlag, Berlin, Heidelberg, 104-109. Available at: [http://dx.doi.org/10.1007/978-3-642-55721-7\\_12](http://dx.doi.org/10.1007/978-3-642-55721-7_12).
- Walesiak, M. (1993), *Statystyczna analiza wielowymiarowa w badaniach marketingowych [Multivariate statistical analysis in marketing research]*. Wrocław University of Economics, Research

Papers no. 654. Available at: [http://keii.ue.wroc.pl/pracownicy/mw/1993\\_Walesiak\\_SAW\\_w\\_badaniach\\_marketingowych\\_OCR.pdf](http://keii.ue.wroc.pl/pracownicy/mw/1993_Walesiak_SAW_w_badaniach_marketingowych_OCR.pdf).

Walesiak, M. (1999), *Distance Measure for Ordinal Data*, "Argumenta Oeconomica", No. 2 (8), 167-173. Available at: [http://keii.ue.wroc.pl/pracownicy/mw/1999\\_Walesiak\\_Argumenta\\_Oeconomica\\_no\\_2.pdf](http://keii.ue.wroc.pl/pracownicy/mw/1999_Walesiak_Argumenta_Oeconomica_no_2.pdf).

Walesiak, M. (2006), *Uogólniona miara odległości w statystycznej analizie wielowymiarowej [The Generalized Distance Measure in multivariate statistical analysis]*, Wydawnictwo AE, Wrocław. Available at: [http://keii.ue.wroc.pl/pracownicy/mw/2006\\_Walesiak\\_Uogolniona\\_miara\\_odleglosci.pdf](http://keii.ue.wroc.pl/pracownicy/mw/2006_Walesiak_Uogolniona_miara_odleglosci.pdf).

Walesiak, M. (2011), *Uogólniona miara odległości GDM w statystycznej analizie wielowymiarowej z wykorzystaniem programu R [The Generalized Distance Measure GDM in multivariate statistical analysis with R]*, Wydawnictwo Uniwersytetu Ekonomicznego, Wrocław. Available at: [http://keii.ue.wroc.pl/pracownicy/mw/2011\\_Walesiak\\_Uogolniona\\_miara\\_odleglosci\\_GDM\\_w\\_SAW\\_z\\_wykorzystaniem\\_programu\\_R\\_errata.pdf](http://keii.ue.wroc.pl/pracownicy/mw/2011_Walesiak_Uogolniona_miara_odleglosci_GDM_w_SAW_z_wykorzystaniem_programu_R_errata.pdf).

Walesiak, M. (2016), *Uogólniona miara odległości GDM w statystycznej analizie wielowymiarowej z wykorzystaniem programu R. Wydanie 2 poprawione i rozszerzone [The Generalized Distance Measure GDM in multivariate statistical analysis with R]*, Wydawnictwo Uniwersytetu Ekonomicznego, Wrocław. Available at: [http://keii.ue.wroc.pl/pracownicy/mw/2016\\_Walesiak\\_Uogolniona\\_miara\\_odleglosci\\_GDM.pdf](http://keii.ue.wroc.pl/pracownicy/mw/2016_Walesiak_Uogolniona_miara_odleglosci_GDM.pdf).

## See Also

[dist.GDM](#)

## Examples

```
# Example 1
library(clusterSim)
data(data_patternGDM2)
res<-pattern.GDM2(data_patternGDM2,
performanceVariable=c("s","s","s","d","d","n"),
nomOptValues=c(NA,NA,NA,NA,NA,3), weightsType<-"equal", weights=NULL,
patternType="lower", patternCoordinates="manual",
patternManual=c("min","min",0,5,"max","max"),
nominalTransfMethod="symmetrical")
print(res)
gdm_p<-res$distances
plot(cbind(gdm_p,gdm_p),xlim=c(max(gdm_p),min(gdm_p)),
ylim=c(min(gdm_p),max(gdm_p)),
xaxt="n",xlab="Order of objects from the best to the worst",
ylab="GDM distances from pattern object", lwd=1.6)
axis(1, at=gdm_p,labels=names(gdm_p), cex.axis=0.5)
```

```
# Example 2
library(clusterSim)
data(data_patternGDM2)
res<-pattern.GDM2(data_patternGDM2,
performanceVariable=c("s","s","s","d","d","n"),
nomOptValues=c(NA,NA,NA,NA,NA,3), weightsType<-"equal", weights=NULL,
patternType="upper", patternCoordinates="dataBounds",
```

```

patternManual=NULL, nominalTransfMethod="database")
print(res)
gdm_p<-res$distances
plot(cbind(gdm_p,gdm_p), xlim=c(min(gdm_p),max(gdm_p)),
ylim=c(min(gdm_p),max(gdm_p)),
xaxt="n",xlab="Order of objects from the best to the worst",
ylab="GDM distances from pattern object", lwd=1.6)
axis(1, at=gdm_p,labels=names(gdm_p), cex.axis=0.5)

```

---

plotCategorical

*Plot categorial data on a scatterplot matrix*


---

### Description

Plot categorial data on a scatterplot matrix (optionally with clusters)

### Usage

```
plotCategorical(x, pairsofVar=NULL, cl=NULL, clColors=NULL,...)
```

### Arguments

x	data matrix (rows correspond to observations and columns correspond to variables)
pairsofVar	pairs of variables - all variables (pairsofVar=NULL) or selected variables, e.g. pairsofVar=c(1,3,4)
cl	cluster membership vector
clColors	The colors of clusters. The colors are given arbitrary (clColors=TRUE) or by hand, e.g. clColors=c("red", "blue", "green"). The number of colors equals the number of clusters
...	Arguments to be passed to methods, such as graphical parameters (see <a href="#">par</a> ).

### Author(s)

Marek Walesiak <marek.walesiak@ue.wroc.pl>, Andrzej Dudek <andrzej.dudek@ue.wroc.pl>

Department of Econometrics and Computer Science, University of Economics, Wroclaw, Poland  
<http://keii.ue.wroc.pl/clusterSim>

### See Also

[plotCategorical3d](#), [colors](#), [pairs](#)

**Examples**

```
# Example 1
library(clusterSim)
data(data_ordinal)
plotCategorical(data_ordinal, pairsofVar=c(1,3,4,9), cl=NULL,
clColors = NULL)

# Example 2
library(clusterSim)
grnd <- cluster.Gen(50,model=5,dataType="o",numCategories=5)
plotCategorical(grnd$data, pairsofVar=NULL, cl=grnd$clusters,
clColors=TRUE)

# Example 3
library(clusterSim)
grnd<-cluster.Gen(50,model=4,dataType="o",numCategories=7, numNoisyVar=2)
plotCategorical(grnd$data, pairsofVar=NULL, cl=grnd$clusters,
clColors = c("red","blue","green"))
```

---

plotCategorical3d      *Plot categorical data with three-dimensional plots*

---

**Description**

Plot categorical data with three-dimensional plots (optionally with clusters)

**Usage**

```
plotCategorical3d(x, tripleofVar=c(1,2,3), cl=NULL, clColors=NULL,...)
```

**Arguments**

x	data matrix (rows correspond to observations and columns correspond to variables)
tripleofVar	triple of variables - vector of the number of variables, e.g. tripleofVar = c(1,3,4)
cl	cluster membership vector
clColors	The colors of clusters. The colors are given arbitrary (clColors=TRUE) or by hand, e.g. clColors=c("red","blue","green"). The number of colors equals the number of clusters
...	Arguments to be passed to methods, such as graphical parameters (see <a href="#">par</a> ).

**Author(s)**

Marek Walesiak <marek.walesiak@ue.wroc.pl>, Andrzej Dudek <andrzej.dudek@ue.wroc.pl>  
Department of Econometrics and Computer Science, University of Economics, Wrocław, Poland  
<http://keii.ue.wroc.pl/clusterSim>

**See Also**[plotCategorical.colors](#)**Examples**

```

# These examples do not run on Mac_OS-X. We're working to fix them
# They run quite well on Windows and Linux in meantime

# Example 1
#library(clusterSim)
#data(data_ordinal)
#plotCategorical3d(data_ordinal, tripleofVar=c(1,3,9), cl=NULL,
#clColors=NULL)

# Example 2
#library(clusterSim)
#grnd <- cluster.Gen(50,model=5,dataType="o",numCategories=5)
#plotCategorical3d(grnd$data, tripleofVar=c(1,2,3), cl=grnd$clusters,
#clColors=TRUE)

# Example 3
#library(clusterSim)
#grnd <- cluster.Gen(50, model=4, dataType="o", numCategories=7, numNoisyVar=2)
#plotCategorical3d(grnd$data, tripleofVar=c(1,2,4), cl=grnd$clusters,
#clColors=c("red", "blue", "green"))

```

plotInterval

*Plot symbolic interval-valued data on a scatterplot matrix***Description**

Plot symbolic interval-valued data on a scatterplot matrix (optionally with clusters)

**Usage**

```
plotInterval(x, pairsofsVar=NULL, cl=NULL, clColors=NULL,...)
```

**Arguments**

x	symbolic interval-valued data
pairsofsVar	pairs of symbolic interval variables - all variables (pairsofsVar=NULL) or selected variables, e.g. pairsofsVar=c(1,3,4)
cl	cluster membership vector
clColors	The colors of clusters. The colors are given arbitrary (clColors=TRUE) or by hand, e.g. clColors=c("red", "blue", "green"). The number of colors equals the number of clusters
...	Arguments to be passed to methods, such as graphical parameters (see <a href="#">par</a> ).

**Author(s)**

Marek Walesiak <marek.walesiak@ue.wroc.pl>, Andrzej Dudek <andrzej.dudek@ue.wroc.pl>  
Department of Econometrics and Computer Science, University of Economics, Wrocław, Poland  
<http://keii.ue.wroc.pl/clusterSim>

**See Also**

[plotCategorical](#), [plotCategorical3d](#), [colors](#), [pairs](#)

**Examples**

```
# Example 1
library(clusterSim)
data(data_symbolic)
plotInterval(data_symbolic, pairsofsVar=c(1,3,4,6), cl=NULL,
             clColors=NULL)

# Example 2
library(clusterSim)
grnd <- cluster.Gen(60, model=5, dataType="s", numNoisyVar=1,
                  numOutliers=10, rangeOutliers=c(1,5))
grnd$clusters[grnd$clusters==0] <- max(grnd$clusters)+1
# To colour outliers
plotInterval(grnd$data, pairsofsVar=NULL, cl=grnd$clusters,
             clColors=TRUE)

# Example 3
library(clusterSim)
grnd <- cluster.Gen(50, model=4, dataType="s", numNoisyVar=2,
                  numOutliers=10, rangeOutliers=c(1,4))
grnd$clusters[grnd$clusters==0] <- max(grnd$clusters)+1
# To colour outliers
plotInterval(grnd$data, pairsofsVar=NULL, cl=grnd$clusters,
             clColors=c("red", "blue", "green", "yellow"))
```

---

replication.Mod

*Modification of replication analysis for cluster validation*

---

**Description**

Modification of replication analysis for cluster validation

**Usage**

```
replication.Mod(x, v="m", u=2, centrotypes="centroids",
               normalization=NULL, distance=NULL, method="kmeans",
               S=10, fixedAsample=NULL)
```

**Arguments**

x	data matrix
v	type of data: metric ("r" - ratio, "i" - interval, "m" - mixed), nonmetric ("o" - ordinal, "n" - multi-state nominal, "b" - binary)
u	number of clusters given arbitrary
centrotypes	"centroids" or "medoids"
normalization	optional, normalization formulas for metric data (normalization by variable): for ratio data: "n0" - without normalization, "n6" - (x/sd), "n6a" - (x/mad), "n7" - (x/range), "n8" - (x/max), "n9" - (x/mean), "n9a" - (x/median), "n10" - (x/sum), "n11" - x/sqrt(SSQ) for interval or mixed data: "n0" - without normalization, "n1" - (x-mean)/sd, "n2" - (x-median)/mad, "n3" - (x-mean)/range, "n3a" - positional unitization (x-median)/range, "n4" - (x-min)/range, "n5" - (x-mean)/max[abs(x-mean)], "n5a" - (x-median)/max[abs(x-median)], "n12" - normalization (x - mean)/(sum(x - mean)^2)^0.5, "n12a" - positional normalization (x - median)/(sum(x - median)^2)^0.5, "n13" - normalization with zero being the central point ((x-midrange)/(range/2))
distance	distance measures NULL for "kmeans" method (based on data matrix), for ratio data: "d1" - Manhattan, "d2" - Euclidean, "d3" - Chebychev (max), "d4" - squared Euclidean, "d5" - GDM1, "d6" - Canberra, "d7" - Bray-Curtis for interval or mixed (ratio & interval) data: "d1", "d2", "d3", "d4", "d5" for ordinal data: "d8" - GDM2 for multi-state nominal: "d9" - Sokal & Michener for binary data: "b1" = Jaccard; "b2" = Sokal & Michener; "b3" = Sokal & Sneath (1); "b4" = Rogers & Tanimoto; "b5" = Czekanowski; "b6" = Gower & Legendre (1); "b7" = Ochiai; "b8" = Sokal & Sneath (2); "b9" = Phi of Pearson; "b10" = Gower & Legendre (2)
method	clustering method: "kmeans" (default), "single", "complete", "average", "mcquitty", "median", "centroid", "ward.D", "ward.D2", "pam", "diana"
S	the number of simulations used to compute mean corrected Rand index
fixedAsample	if NULL A sample is generated randomly, otherwise this parameter contains object numbers arbitrarily assigned to A sample

**Details**

See file [../doc/replication.Mod\\_details.pdf](#) for further details

**Value**

A	3-dimensional array containing data matrices for A sample of objects in each simulation (first dimension represents simulation number, second - object number, third - variable number)
B	3-dimensional array containing data matrices for B sample of objects in each simulation (first dimension represents simulation number, second - object number, third - variable number)



centroid	3-dimensional array containing centroids of u clusters for A sample of objects in each simulation (first dimension represents simulation number, second - cluster number, third - variable number)
medoid	3-dimensional array containing matrices of observations on u representative objects (medoids) for A sample of objects in each simulation (first dimension represents simulation number, second - cluster number, third - variable number)
clusteringA	2-dimensional array containing cluster numbers for A sample of objects in each simulation (first dimension represents simulation number, second - object number)
clusteringB	2-dimensional array containing cluster numbers for B sample of objects in each simulation (first dimension represents simulation number, second - object number)
clusteringBB	2-dimensional array containing cluster numbers for B sample of objects in each simulation according to 4 step of replication analysis procedure (first dimension represents simulation number, second - object number)
cRand	value of mean corrected Rand index for S simulations

**Author(s)**

Marek Walesiak <marek.walesiak@ue.wroc.pl>, Andrzej Dudek <andrzej.dudek@ue.wroc.pl>  
 Department of Econometrics and Computer Science, University of Economics, Wroclaw, Poland  
<http://keii.ue.wroc.pl/clusterSim>

**References**

- Breckenridge, J.N. (2000), *Validating cluster analysis: consistent replication and symmetry*, "Multivariate Behavioral Research", 35 (2), 261-285. Available at: [http://dx.doi.org/10.1207/S15327906MBR3502\\_5](http://dx.doi.org/10.1207/S15327906MBR3502_5).
- Gordon, A.D. (1999), *Classification*, Chapman and Hall/CRC, London. ISBN 9781584880134.
- Hubert, L., Arabie, P. (1985), *Comparing partitions*, "Journal of Classification", no. 1, 193-218. Available at: <http://dx.doi.org/10.1007%2FBF01908075>.
- Milligan, G.W. (1996), *Clustering validation: results and implications for applied analyses*, In P. Arabie, L.J. Hubert, G. de Soete (Eds.), *Clustering and classification*, World Scientific, Singapore, 341-375. ISBN 9789810212872.
- Walesiak, M. (2008), *Ocena stabilnosci wyników klasyfikacji z wykorzystaniem analizy replikacji*, In: J. Pocięcha (Ed.), *Modelowanie i prognozowanie zjawisk społeczno-gospodarczych*, Wydawnictwo AE, Krakow, 67-72. Available at: [http://keii.ue.wroc.pl/pracownicy/mw/2008\\_Walesiak\\_Ocena\\_stabilnosci\\_wynikow\\_klasyfikacji.pdf](http://keii.ue.wroc.pl/pracownicy/mw/2008_Walesiak_Ocena_stabilnosci_wynikow_klasyfikacji.pdf).

**See Also**

[cluster.Sim](#), [hclust](#), [kmeans](#), [dist](#), [dist.BC](#), [dist.SM](#), [dist.GDM](#),  
[data.Normalization](#)

**Examples**

```

library(clusterSim)
data(data_ratio)
w <- replication.Mod(data_ratio, u=5, S=10)
print(w)

library(clusterSim)
data(data_binary)
replication.Mod(data_binary,"b", u=2, "medoids", NULL,"b1", "pam", fixedAsample=c(1,3,6,7))

```

---

shapes.blocks3d	<i>Generation of data set containing two clusters with untypical shapes (cube divided into two parts by main diagonal plane)</i>
-----------------	--

---

**Description**

Generation of data set containing two clusters with untypical shapes (cube starting at point (0,0,0) divided into two parts by main diagonal plane)

**Usage**

```

shapes.blocks3d(numObjects=180,shapesUnitSize=0.5, shape2coordinateX=1.2,
shape2coordinateY=1.2,shape2coordinateZ=1.2, outputCsv="", outputCsv2="",
outputColNames=TRUE, outputRowNames=TRUE)

```

**Arguments**

numObjects	number of objects in each cluster - positive integer value or vector with length=2
shapesUnitSize	length of one unit for shape (maximal height, width and depth of shape is 2*shapesUnitSize)
shape2coordinateX	maximal value for second shape in first (X) dimension
shape2coordinateY	maximal value for second shape in second (Y) dimension
shape2coordinateZ	maximal value for second shape in third (Z) dimension
outputCsv	optional, name of csv file with generated data (first column contains id, second - number of cluster and others - data)
outputCsv2	optional, name of csv (a comma as decimal point and a semicolon as field separator) file with generated data (first column contains id, second - number of cluster and others - data)
outputColNames	outputColNames=TRUE indicates that output file (given by outputCsv and outputCsv2 parameters) contains first row with column names
outputRowNames	outputRowNames=TRUE indicates that output file (given by outputCsv and outputCsv2 parameters) contains a vector of row names

**Value**

clusters            cluster number for each object  
 data                generated data - matrix with objects in rows and variables in columns

**Author(s)**

Marek Walesiak <marek.walesiak@ue.wroc.pl>, Andrzej Dudek <andrzej.dudek@ue.wroc.pl>  
 Department of Econometrics and Computer Science, University of Economics, Wrocław, Poland  
<http://keii.ue.wroc.pl/clusterSim>

**See Also**

[shapes.worms](#), [shapes.circles2](#), [shapes.circles3](#), [shapes.bulls.ey](#), [shapes.two.moon](#)

**Examples**

```
library(clusterSim)
library(rgl)
sb3d<-shapes.blocks3d(300,1,3,3,3)
plot3d(sb3d$data, col=rainbow(2)[sb3d$clusters])
```

---

shades.circles2	<i>Generation of data set containing two clusters with untypical ring shapes (circles)</i>
-----------------	--

---

**Description**

Generation of data set containing two clusters with untypical ring shapes. For each point first random radius  $r$  from given interval is generated then random angle  $\alpha$  and finally the coordinates of point are calculated as  $(r \cdot \cos(\alpha), r \cdot \sin(\alpha))$ . For bull's eye data set second shape is filled circle ( $r$  starts from 0)

**Usage**

```
shades.circles2(numObjects=180, shape1rFrom=0.75, shape1rTo=0.9, shape2rFrom=0.35,
  shape2rTo=0.5, outputCsv="", outputCsv2="", outputColNames=TRUE, outputRowNames=TRUE)
shades.bulls.ey(numObjects=180, shape1rFrom=0.75, shape1rTo=0.95, shape2rTo=0.45,
  outputCsv="", outputCsv2="", outputColNames=TRUE, outputRowNames=TRUE)
```

**Arguments**

numObjects        number of objects in each cluster - positive integer value or vector with length=2,  
 shape1rFrom      minimal value of radius for first ring  
 shape1rTo        maximal value of radius for first ring  
 shape2rFrom      minimal value of radius for second ring  
 shape2rTo        maximal value of radius for second ring

outputCsv	optional, name of csv file with generated data (first column contains id, second - number of cluster and others - data)
outputCsv2	optional, name of csv (a comma as decimal point and a semicolon as field separator) file with generated data (first column contains id, second - number of cluster and others - data)
outputColNames	outputColNames=TRUE indicates that output file (given by outputCsv and outputCsv2 parameters) contains first row with column names
outputRowNames	outputRowNames=TRUE indicates that output file (given by outputCsv and outputCsv2 parameters) contains a vector of row names

**Value**

clusters	cluster number for each object
data	generated data - matrix with objects in rows and variables in columns

**Author(s)**

Marek Walesiak <marek.walesiak@ue.wroc.pl>, Andrzej Dudek <andrzej.dudek@ue.wroc.pl>  
 Department of Econometrics and Computer Science, University of Economics, Wrocław, Poland  
<http://keii.ue.wroc.pl/clusterSim>

**See Also**

[shapes.worms](#), [shapes.circles3](#), [shapes.bulls.eyes](#), [shapes.two.moon](#), [shapes.blocks3d](#)

**Examples**

```
#Example1
library(clusterSim)
sc2<-shapes.circles2(180)
plot(sc2$data,col=rainbow(2)[sc2$clusters])

#Example2
library(clusterSim)
sbe<-shapes.bulls.eyes(numObjects=c(120,60))
plot(sbe$data,col=rainbow(2)[sbe$clusters])
```

---

shapes.circles3	<i>Generation of data set containing three clusters with untypical ring shapes (circles)</i>
-----------------	--

---

**Description**

Generation of data set containing three clusters with untypical ring shapes. For each point first random radius  $r$  from given interval is generated then random angle  $\alpha$  and finally the coordinates of point are calculated as  $(r \cdot \cos(\alpha), r \cdot \sin(\alpha))$

**Usage**

```
shapes.circles3(numObjects=180,shape1rFrom=0.15,shape1rTo=0.3,
shape2rFrom=0.55,shape2rTo=0.7,shape3rFrom=1.15,shape3rTo=1.3,
outputCsv="", outputCsv2="", outputColNames=TRUE, outputRowNames=TRUE)
```

**Arguments**

numObjects	number of objects in each cluster - positive integer value or vector with length=3,
shape1rFrom	minimal value of radius for first ring
shape1rTo	maximal value of radius for first ring
shape2rFrom	minimal value of radius for second ring
shape2rTo	maximal value of radius for second ring
shape3rFrom	minimal value of radius for third ring
shape3rTo	maximal value of radius for third ring
outputCsv	optional, name of csv file with generated data (first column contains id, second - number of cluster and others - data)
outputCsv2	optional, name of csv (a comma as decimal point and a semicolon as field separator) file with generated data (first column contains id, second - number of cluster and others - data)
outputColNames	outputColNames=TRUE indicates that output file (given by outputCsv and outputCsv2 parameters) contains first row with column names
outputRowNames	outputRowNames=TRUE indicates that output file (given by outputCsv and outputCsv2 parameters) contains a vector of row names

**Value**

clusters	cluster number for each object
data	generated data - matrix with objects in rows and variables in columns

**Author(s)**

Marek Walesiak <marek.walesiak@ue.wroc.pl>, Andrzej Dudek <andrzej.dudek@ue.wroc.pl>  
 Department of Econometrics and Computer Science, University of Economics, Wrocław, Poland  
<http://keii.ue.wroc.pl/clusterSim>

**See Also**

[shapes.worms](#),[shapes.circles2](#),[shapes.bulls.eyes](#),[shapes.two.moon](#),[shapes.blocks3d](#)

**Examples**

```
#Example1
library(clusterSim)
sc3a<-shapes.circles3(180)
plot(sc3a$data,col=rainbow(3)[sc3a$clusters])
```

```
#Example2
library(clusterSim)
sc3b<-shapes.circles3(numObjects=c(120,180,240))
plot(sc3b$data,col=rainbow(3)[sc3b$clusters])
```

---

shapes.two.moon      *Generation of data set containing two clusters with untypical shapes (similar to waxing and waning crescent moon)*

---

## Description

Generation of data set containing two clusters with untypical shapes (similar to waxing and waning crescent moon). For each point first random radius  $r$  from given interval is generated then random angle  $\alpha$  and finally the coordinates of point are calculated as  $(a+\text{abs}(r*\cos(\alpha)),r*\sin(\alpha))$  for first shape and  $(-\text{abs}(r*\cos(\alpha)),r*\sin(\alpha)-b)$  for second shape

## Usage

```
shapes.two.moon(numObjects=180,shape1a=-0.4,shape2b=1,shape1rFrom=0.8,
shape1rTo=1.2,shape2rFrom=0.8, shape2rTo=1.2, outputCsv="", outputCsv2="",
outputColNames=TRUE, outputRowNames=TRUE)
```

## Arguments

numObjects	number of objects in each cluster - positive integer value or vector with length=2,
shape1a	parameter a for first shape
shape2b	parameter b for first shape
shape1rFrom	minimal value of radius for first shape
shape1rTo	maximal value of radius for first shape
shape2rFrom	minimal value of radius for second shape
shape2rTo	maximal value of radius for second shape
outputCsv	optional, name of csv file with generated data (first column contains id, second - number of cluster and others - data)
outputCsv2	optional, name of csv (a comma as decimal point and a semicolon as field separator) file with generated data (first column contains id, second - number of cluster and others - data)
outputColNames	outputColNames=TRUE indicates that output file (given by outputCsv and outputCsv2 parameters) contains first row with column names
outputRowNames	outputRowNames=TRUE indicates that output file (given by outputCsv and outputCsv2 parameters) contains a vector of row names

## Value

clusters	cluster number for each object
data	generated data - matrix with objects in rows and variables in columns

**Author(s)**

Marek Walesiak <marek.walesiak@ue.wroc.pl>, Andrzej Dudek <andrzej.dudek@ue.wroc.pl>  
 Department of Econometrics and Computer Science, University of Economics, Wrocław, Poland  
<http://keii.ue.wroc.pl/clusterSim>

**See Also**

[shapes.worms](#), [shapes.circles2](#), [shapes.circles3](#), [shapes.bulls.eyes](#), [shapes.blocks3d](#)

**Examples**

```
library(clusterSim)
stm<-shapes.two.moon(180)
plot(stm$data,col=rainbow(2)[stm$clusters])
```

---

shapes.worms	<i>Generation of data set containing two clusters with untypical parabolic shapes (worms)</i>
--------------	---

---

**Description**

Generation of data set containing two clusters with untypical parabolic shapes (first is given by  $y=x^2$ , second by  $y=-(x-a)^2+b$  with distortion from  $\langle -tol,+tol \rangle$ )

**Usage**

```
shapes.worms(numObjects=180, shape1x1=-2, shape1x2=2, shape2x1=-0.5,
  shape2x2=2.5, shape2a=1.5, shape2b=5.5, tol=0.1, outputCsv="", outputCsv2="",
  outputColNames=TRUE, outputRowNames=TRUE)
```

**Arguments**

numObjects	number of objects in each cluster - positive integer value or vector with length=2
shape1x1	starting value on abscissa axis for shape 1
shape1x2	end value on abscissa axis for shape 1
shape2x1	starting value on abscissa axis for shape 2
shape2x2	end value on abscissa axis for shape 2
shape2a	parameter a of shape 2
shape2b	parameter b of shape 2
tol	tolerance - each generated point is randomized by adding $\text{runif}(1,0,\text{tol})$
outputCsv	optional, name of csv file with generated data (first column contains id, second - number of cluster and others - data)
outputCsv2	optional, name of csv (a comma as decimal point and a semicolon as field separator) file with generated data (first column contains id, second - number of cluster and others - data)

outputColNames outputColNames=TRUE indicates that output file (given by outputCsv and outputCsv2 parameters) contains first row with column names

outputRowNames outputRowNames=TRUE indicates that output file (given by outputCsv and outputCsv2 parameters) contains a vector of row names

**Value**

clusters cluster number for each object

data generated data - matrix with objects in rows and variables in columns

**Author(s)**

Marek Walesiak <marek.walesiak@ue.wroc.pl>, Andrzej Dudek <andrzej.dudek@ue.wroc.pl>  
 Department of Econometrics and Computer Science, University of Economics, Wroclaw, Poland  
<http://keii.ue.wroc.pl/clusterSim>

**See Also**

[shapes.worms](#), [shapes.circles2](#), [shapes.circles3](#), [shapes.bulls.ey](#), [shapes.two.moon](#), [shapes.blocks3d](#)

**Examples**

```
library(clusterSim)
sw<-shapes.worms(180)
plot(sw$data,col=rainbow(2)[sw$clusters])
```

---

specc1 *A spectral clustering algorithm*

---

**Description**

A spectral clustering algorithm. Cluster analysis is performed by embedding the data into the subspace of the eigenvectors of an affinity matrix

**Usage**

```
specc1(data,nc,distance="GDM1",sigma="automatic",sigma.interval="default",
mod.sample=0.75,R=10,iterations=3,na.action=na.omit,...)
```

**Arguments**

data matrix or dataset

nc the number of clusters



distance	distance function used to calculate affinity matrix: "sEuclidean" - squared Euclidean distance, "euclidean" - Euclidean distance, "manhattan" - city block distance, "maximum" - Chebyshev distance, "canberra" - Lance and Williams Canberra distance, "BC" - Bray-Curtis distance measure for ratio data, "GDM1" - GDM distance for metric data, "GDM2" - GDM distance for ordinal data, "SM" - Sokal-Michener distance measure for nominal variables
sigma	scale parameter used to calculate affinity matrix: sigma="automatic" - an algorithm for searching optimal value of sigma parameter; sigma=200 - value of sigma parameter given by researcher, e.g. 200
sigma.interval	sigma.interval="default" - from zero to square root of sum of all distances in lower triangle of distance matrix for "sEuclidean" and from zero to sum of all distances in lower triangle of distance matrix for other distances; sigma.interval=1000 - from zero to value given by researcher, e.g. 1000
mod.sample	proportion of data to use when estimating sigma (default: 0.75)
R	the number of intervals examined in each step of searching optimal value of sigma parameter algorithm (See <a href="#">../doc/speccl_details.pdf</a> )
iterations	the maximum number of iterations (rounds) allowed in algorithm of searching optimal value of sigma parameter
na.action	the action to perform on NA
...	arguments passed to kmeans procedure

### Details

See file [../doc/speccl\\_details.pdf](#) for further details

### Value

scdist	returns the lower triangle of the distance matrix
clusters	a vector of integers indicating the cluster to which each object is allocated
size	the number of objects in each cluster
withinss	the within-cluster sum of squared distances for each cluster
Ematrix	data matrix $n \times u$ ( $n$ - the number of objects, $u$ - the number of eigenvectors)
Ymatrix	normalized data matrix $n \times u$ ( $n$ - the number of objects, $u$ - the number of eigenvectors)
sigma	the value of scale parameter given by searching algorithm

### Author(s)

Marek Walesiak <[marek.walesiak@ue.wroc.pl](mailto:marek.walesiak@ue.wroc.pl)>, Andrzej Dudek <[andrzej.dudek@ue.wroc.pl](mailto:andrzej.dudek@ue.wroc.pl)>  
 Department of Econometrics and Computer Science, Wrocław University of Economics, Poland  
<http://keii.ue.wroc.pl/clusterSim>

## References

Karatzoglou, A. (2006), *Kernel methods. Software, algorithms and applications*, Dissertation, Wien, Technical University.

Ng, A., Jordan, M., Weiss, Y. (2002), *On spectral clustering: analysis and an algorithm*, In: T. Dietterich, S. Becker, Z. Ghahramani (Eds.), *Advances in Neural Information Processing Systems* 14. MIT Press, 849-856. Available at:

<https://papers.nips.cc/paper/2092-on-spectral-clustering-analysis-and-an-algorithm.pdf>.

Walesiak, M. (2011), *Uogólniona miara odległości GDM w statystycznej analizie wielowymiarowej z wykorzystaniem programu R [The Generalized Distance Measure GDM in multivariate statistical analysis with R]*, Wydawnictwo Uniwersytetu Ekonomicznego, Wrocław. Available at: [http://keii.ue.wroc.pl/pracownicy/mw/2011\\_Walesiak\\_Uogolniona\\_miara\\_odleglosci\\_GDM\\_w\\_SAW\\_z\\_wykorzystaniem\\_programu\\_R\\_errata.pdf](http://keii.ue.wroc.pl/pracownicy/mw/2011_Walesiak_Uogolniona_miara_odleglosci_GDM_w_SAW_z_wykorzystaniem_programu_R_errata.pdf).

Walesiak, M. (2012), *Klasyfikacja spektralna a skale pomiaru zmiennych [Spectral clustering and measurement scales of variables]*, *Przegląd Statystyczny (Statistical Review)*, no. 1, 13-31. Available at: [http://keii.ue.wroc.pl/pracownicy/mw/2012\\_Walesiak\\_Przeglad\\_Statystyczny\\_z\\_1.pdf](http://keii.ue.wroc.pl/pracownicy/mw/2012_Walesiak_Przeglad_Statystyczny_z_1.pdf).

Walesiak, M. (2016), *Uogólniona miara odległości GDM w statystycznej analizie wielowymiarowej z wykorzystaniem programu R. Wydanie 2 poprawione i rozszerzone [The Generalized Distance Measure GDM in multivariate statistical analysis with R]*, Wydawnictwo Uniwersytetu Ekonomicznego, Wrocław. Available at: [http://keii.ue.wroc.pl/pracownicy/mw/2016\\_Walesiak\\_Uogolniona\\_miara\\_odleglosci\\_GDM.pdf](http://keii.ue.wroc.pl/pracownicy/mw/2016_Walesiak_Uogolniona_miara_odleglosci_GDM.pdf).

## See Also

[dist.GDM](#), [kmeans](#), [dist](#), [dist.binary](#), [dist.SM](#), [dist.BC](#)

## Examples

```
# Commented due to long execution time
# Example 1
#library(clusterSim)
#library(mlbench)
#data<-mlbench.spirals(100,1,0.03)
#plot(data)
#x<-data$x
#res1<-speccl(x,nc=2,distance="GDM1",sigma="automatic",
#sigma.interval="default",mod.sample=0.75,R=10,iterations=3)
#clas1<-res1$cluster
#print(data$classes)
#print(clas1)
#cRand<-classAgreement(table(as.numeric(as.vector(data$classes)),
#res1$clusters))$crand
#print(res1$sigma)
#print(cRand)

# Example 2
#library(clusterSim)
```

```
#grnd2<-cluster.Gen(50,model=4,dataType="m",numNoisyVar=1)
#data<-as.matrix(grnd2$data)
#colornames<-c("red","blue","green")
#grnd2$clusters[grnd2$clusters==0]<-length(colornames)
#plot(grnd2$data,col=colornames[grnd2$clusters])
#us<-nrow(data)*nrow(data)/2
#res2<-speccl(data,nc=3,distance="sEuclidean",sigma="automatic",
#sigma.interval=us,mod.sample=0.75,R=10,iterations=3)
#cRand<-comparing.Partitions(grnd2$clusters,res2$clusters,type="crand")
#print(res2$sigma)
#print(cRand)

# Example 3
#library(clusterSim)
#grnd3<-cluster.Gen(40,model=4,dataType="o",numCategories=7)
#data<-as.matrix(grnd3$data)
#plotCategorical(grnd3$data,pairsofVar=NULL,cl=grnd3$clusters,
#c1Colors=c("red","blue","green"))
#res3<-speccl(data,nc=3,distance="GDM2",sigma="automatic",
#sigma.interval="default",mod.sample=0.75,R=10,iterations=3)
#cRand<-comparing.Partitions(grnd3$clusters,res3$clusters,type="crand")
#print(res3$sigma)
#print(cRand)

# Example 4
library(clusterSim)
data(data_nominal)
res4<-speccl(data_nominal,nc=4,distance="SM",sigma="automatic",
sigma.interval="default",mod.sample=0.75,R=10,iterations=3)
print(res4)
```

# Index

- \* **GDM distance**
  - ordinalToMetric, 52
- \* **cluster analysis**
  - specc1, 72
- \* **cluster**
  - cluster.Description, 3
  - cluster.Gen, 4
  - cluster.Sim, 8
  - comparing.Partitions, 10
  - data.Normalization, 12
  - dist.BC, 21
  - dist.GDM, 22
  - dist.SM, 24
  - HINoV.Mod, 26
  - HINoV.Symbolic, 28
  - index.C, 30
  - index.DB, 32
  - index.G1, 34
  - index.G2, 36
  - index.G3, 37
  - index.Gap, 39
  - index.H, 42
  - index.KL, 45
  - index.S, 47
  - initial.Centers, 49
  - pattern.GDM1, 53
  - pattern.GDM2, 57
  - replication.Mod, 63
  - shapes.blocks3d, 66
  - shapes.circles2, 67
  - shapes.circles3, 68
  - shapes.two.moon, 70
  - shapes.worms, 71
- \* **data set**
  - data\_symbolic\_interval\_polish\_voivodships, 20
- \* **datasets**
  - data\_binary, 14
  - data\_interval, 14
  - data\_mixed, 15
  - data\_nominal, 15
  - data\_ordinal, 16
  - data\_patternGDM1, 16
  - data\_patternGDM2, 18
  - data\_ratio, 19
  - data\_symbolic, 20
- \* **dataset**
  - shapes.blocks3d, 66
  - shapes.circles2, 67
  - shapes.circles3, 68
  - shapes.two.moon, 70
  - shapes.worms, 71
- \* **data**
  - cluster.Gen, 4
  - cluster.Sim, 8
- \* **distances for interval-valued data**
  - dist.Symbolic, 25
- \* **hplot**
  - plotCategorical, 60
  - plotCategorical3d, 61
  - plotInterval, 62
- \* **interval-valued data**
  - dist.Symbolic, 25
  - interval\_normalization, 50
- \* **multivariate statistical analysis**
  - ordinalToMetric, 52
- \* **multivariate**
  - cluster.Gen, 4
  - cluster.Sim, 8
  - replication.Mod, 63
- \* **normalization**
  - interval\_normalization, 50
- \* **optimize**
  - cluster.Sim, 8
- \* **ordinal scale**
  - ordinalToMetric, 52
- \* **reinforcing measurement scale**
  - ordinalToMetric, 52

- \* **scales of measurement**
  - specc1, 72
- \* **spectral clustering**
  - specc1, 72
- \* **symbolic data analysis**
  - dist.Symbolic, 25
  - interval\_normalization, 50
  
- cluster.Description, 3
- cluster.Gen, 4
- cluster.Sim, 4, 8, 14, 28, 30, 49, 65
- colors, 60, 62, 63
- comparing.Partitions, 10
  
- data.Normalization, 10, 12, 51, 56, 65
- data\_binary, 14
- data\_interval, 14
- data\_mixed, 15
- data\_nominal, 15
- data\_ordinal, 16
- data\_patternGDM1, 16
- data\_patternGDM2, 18
- data\_ratio, 19
- data\_symbolic, 20
- data\_symbolic\_interval\_polish\_voivodships, 20
- dist, 10, 22, 23, 25, 28, 65, 74
- dist.BC, 10, 21, 23, 25, 28, 65, 74
- dist.binary, 74
- dist.GDM, 10, 22, 22, 25, 28, 53, 56, 59, 65, 74
- dist.SM, 10, 22, 23, 24, 28, 65, 74
- dist.Symbolic, 25
  
- GDM (dist.GDM), 22
- GDM1 (dist.GDM), 22
- GDM2 (dist.GDM), 22
  
- hclust, 10, 28, 30, 65
- HINoV.Mod, 26
- HINoV.Symbolic, 28
  
- index.C, 10, 30, 30, 33, 35, 37, 38, 40, 43, 45, 48
- index.DB, 31, 32, 35, 37, 38, 40, 43, 45, 48
- index.G1, 10, 31, 33, 34, 37, 38, 40, 43, 45, 48
- index.G2, 10, 31, 33, 35, 36, 38, 40, 43, 45, 48
- index.G3, 10, 30, 31, 33, 35, 37, 37, 40, 43, 45, 48
- index.Gap, 31, 33, 35, 37, 38, 39, 43, 45, 48
  
- index.H, 31, 33, 35, 37, 38, 40, 42, 45, 48
- index.KL, 10, 31, 33, 35, 37, 38, 40, 43, 45, 48
- index.S, 10, 31, 33, 35, 37, 38, 40, 43, 45, 47
- initial.Centers, 49
- interval\_normalization, 50
  
- kmeans, 28, 30, 65, 74
  
- mad, 4
- mean, 4
- median, 4
  
- ordinalToMetric, 52
  
- pairs, 60, 63
- par, 60–62
- pattern.GDM1, 53
- pattern.GDM2, 57
- plotCategorical, 60, 62, 63
- plotCategorical3d, 60, 61, 63
- plotInterval, 62
  
- replication.Mod, 11, 63
  
- sd, 4
- shapes.blocks3d, 66, 68, 69, 71, 72
- shapes.bulls.eye, 67–69, 71, 72
- shapes.bulls.eye (shapes.circles2), 67
- shapes.circles2, 67, 67, 69, 71, 72
- shapes.circles3, 67, 68, 68, 71, 72
- shapes.two.moon, 67–69, 70, 72
- shapes.worms, 67–69, 71, 71, 72
- specc1, 72