

# Package ‘plot3logit’

September 12, 2020

**Type** Package

**Title** Ternary Plots for Trinomial Regression Models

**Version** 3.0.0

**Author** Flavio Santi [cre, aut] (<<https://orcid.org/0000-0002-2014-1981>>),  
Maria Michela Dickson [aut] (<<https://orcid.org/0000-0002-4307-0469>>),  
Giuseppe Espa [aut] (<<https://orcid.org/0000-0002-0331-3630>>),  
Diego Giuliani [aut] (<<https://orcid.org/0000-0002-7198-6714>>)

**Maintainer** Flavio Santi <[flavio.santi@univr.it](mailto:flavio.santi@univr.it)>

**URL** <https://www.flaviosanti.it/software/plot3logit>

**BugReports** <https://github.com/f-santi/plot3logit/issues>

**Description** An implementation of the ternary plot for interpreting regression coefficients of trinomial regression models, as proposed in Santi, Dickson and Espa (2019) <[doi:10.1080/00031305.2018.1442368](https://doi.org/10.1080/00031305.2018.1442368)>. Ternary plots can be drawn using either 'ggtern' package (based on 'ggplot2') or 'Ternary' package (based on standard graphics).

**Depends** R (>= 3.5), ggtern (>= 3.3.0), Ternary (>= 1.0.1)

**Imports** dplyr, ellipse, forcats, generics, ggplot2 (>= 3.3.0),  
graphics, grDevices, lifecycle, magrittr (>= 1.5), purrr,  
Rdpack, stats, stringr, tibble, tidyr, tidyselect, utils

**Suggests** knitr, MASS (>= 7.3-51), mlogit, nnet, ordinal, rmarkdown,  
VGAM, testthat

**License** GPL (>= 2)

**LazyData** true

**NeedsCompilation** no

**Encoding** UTF-8

**RoxygenNote** 7.1.0

**Repository** CRAN

**VignetteBuilder** knitr

**RdMacros** Rdpack, lifecycle

**Date/Publication** 2020-09-12 08:40:02 UTC

## R topics documented:

|                      |           |
|----------------------|-----------|
| plot3logit-package   | 2         |
| add_confregions      | 4         |
| autoplot.field3logit | 5         |
| cross_1year          | 6         |
| extract3logit        | 7         |
| field3logit          | 8         |
| gg3logit             | 12        |
| labels               | 14        |
| multifield3logit     | 14        |
| stat_3logit          | 16        |
| stat_conf3logit      | 18        |
| stat_field3logit     | 19        |
| TernaryField         | 20        |
| USvote2016           | 21        |
| <b>Index</b>         | <b>23</b> |

---

plot3logit-package      *Ternary Plots for Trinomial Regression Models*

---

### Description

An implementation of the ternary plot for interpreting regression coefficients of trinomial regression models, as proposed in Santi et al. (2019).

### Details

The package permits the covariate effects of trinomial regression models to be represented graphically by means of a ternary plot. The aim of the plots is helping the interpretation of regression coefficients in terms of the effects that a change in regressors' values has on the probability distribution of the dependent variable. Such changes may involve either a single regressor, or a group of them (composite changes), and the package permits both cases to be represented in a user-friendly way. Methodological details are illustrated and discussed in Santi et al. (2019).

The package can read the results of **both categorical and ordinal trinomial logit** regression fitted by various functions (see `extract3logit()`) and creates a `field3logit` object which may be represented by means of functions `autoplot()` and `plot()`.

The `plot3logit` package inherits graphical classes and methods from the package `ggtern` (Hamilton and Ferry 2018) which, in turn, is based on the `ggplot2` package (Wickham 2016).

Graphical representation based on **standard graphics** is made available through the package `Ternary` (Smith 2017) by function `TernaryField()` and in particular by the method `plot` of `field3logit` class.

Since version 2.0.0, `plot3logit` can also compute and draw confidence regions associated to the covariate effects. See the vignette of the package (type `vignette('plot3logit-overview')`) and the help of function `stat_conf3logit()` for some examples.

## Compatibility

Function `field3logit()` can read trinomial regression estimates from the output of the following functions:

- `clm` and `clm2` of package `ordinal` (ordinal logit regression);
- `mlogit` of package `mlogit` (logit regression);
- `multinom` of package `nnet` (logit regression);
- `polr` of package `MASS` (ordinal logit regression);
- `vglm` and `vglm` of package `VGAM` (logit regression).

Moreover, explicit estimates can be passed to `field3logit()`. See examples and functions `field3logit()` and `extract3logit()` for further details.

## References

Hamilton NE, Ferry M (2018). “ggtern: Ternary Diagrams Using ggplot2.” *Journal of Statistical Software, Code Snippets*, **87**(3), 1-17. doi: [10.18637/jss.v087.c03](https://doi.org/10.18637/jss.v087.c03).

Santi F, Dickson MM, Espa G (2019). “A graphical tool for interpreting regression coefficients of trinomial logit models.” *The American Statistician*, **73**(2), 200-207. doi: [10.1080/00031305.2018.1442368](https://doi.org/10.1080/00031305.2018.1442368).

Smith MR (2017). “Ternary: An R Package for Creating Ternary Plots.” *Zenodo*.

Wickham H (2016). *ggplot2: Elegant Graphics for Data Analysis*. Springer-Verlag. ISBN 978-3-319-24277-4.

## See Also

`field3logit()`, `gg3logit()`, `TernaryField()`.

## Examples

```
## Not run:
data(cross_1year)

# Read from "nnet::multinom" (categorical logit)
library(nnet)
mod0 <- multinom(employment_sit ~ gender + finalgrade, data = cross_1year)
field0 <- field3logit(mod0, 'genderFemale')
gg3logit(field0) + stat_field3logit()

# Read from "MASS::polr" (ordinal logit)
library(MASS)
mydata <- cross_1year
mydata$finalgrade <- factor(mydata$finalgrade,
  c('Low', 'Average', 'High'), ordered = TRUE)
mod1 <- polr(finalgrade ~ gender + irregularity, data = mydata)
field1 <- field3logit(mod1, 'genderFemale')
gg3logit(field1) + stat_field3logit()
```

```

# Read from list
mod2 <- list(
  B = matrix(
    data = c(-2.05, 0.46, -2.46, 0.37),
    nrow = 2,
    dimnames = list(c('Intercept'), 'genderFemale'))
  ),
  levels = c('Employed', 'Unemployed', 'Trainee')
)
field2 <- field3logit(mod2, c(0, 1))
gg3logit(field2) + stat_field3logit()

## End(Not run)

```

---

|                 |  |
|-----------------|--|
| add_confregions | <i>Compute the confidence regions of covariate effects</i> |
|-----------------|--|

---

### Description

Given the confidence level, it computes the confidence regions of the effects for each arrow of the `field3logit` or `multifield3logit` object given in input. If the `field3logit` or `multifield3logit` object already contains the confidence regions, they will be updated if the value of `conf` is different.

### Usage

```
add_confregions(x, conf = 0.95, npoints = 100)
```

### Arguments

|                      |  |
|----------------------|--|
| <code>x</code>       | an object of class <code>field3logit</code> or <code>multifield3logit</code> . |
| <code>conf</code>    | confidence level of the regions.   |
| <code>npoints</code> | number of points of the borders of the regions.                                |

### Value

Object of class `field3logit` or `multifield3logit` with updated confidence regions.

### Examples

```

data(cross_1year)

mod0 <- nnet::multinom(employment_sit ~ gender + finalgrade,
  data = cross_1year)
field0 <- field3logit(mod0, 'genderFemale')
field0
add_confregions(field0)

```

---

autoplot.field3logit *Create a gg3logit plot with field and confidence regions*

---

### Description

`autoplot()` creates a `gg3logit` plot and adds a field and its confidence regions. `autoplot()` is a wrapper for `gg3logit()` and `stat_3logit()`.

### Usage

```
## S3 method for class 'field3logit'
autoplot(
  object,
  ...,
  mapping_field = aes(),
  mapping_conf = aes(),
  data = NULL,
  params_field = list(),
  params_conf = list(),
  show.legend = NA,
  conf = TRUE
)
```

### Arguments

|                            |  |
|----------------------------|--|
| <code>object</code>        | an object of class <code>field3logit</code> or <code>multifield3logit</code> .   |
| <code>...</code>           | other arguments passed to specific methods   |
| <code>mapping_field</code> | aesthetic mappings passed to argument mapping of <code>stat_field3logit()</code> and <code>stat_conf3logit()</code> .  |
| <code>mapping_conf</code>  | aesthetic mappings passed to argument mapping of <code>stat_field3logit()</code> and <code>stat_conf3logit()</code> .  |
| <code>data</code>          | a <code>field3logit</code> object, a <code>multifield3logit</code> object, or a <code>data.frame</code> structured like a fortified <code>field3logit</code> or a <code>multifield3logit</code> object.  |
| <code>params_field</code>  | graphical parameters passed to argument mapping of <code>stat_field3logit()</code> and <code>stat_conf3logit()</code> .  |
| <code>params_conf</code>   | graphical parameters passed to argument mapping of <code>stat_field3logit()</code> and <code>stat_conf3logit()</code> .  |
| <code>show.legend</code>   | logical. Should this layer be included in the legends? <code>NA</code> , the default, includes if any aesthetics are mapped. <code>FALSE</code> never includes, and <code>TRUE</code> always includes. It can also be a named logical vector to finely select the aesthetics to display. |
| <code>conf</code>          | if <code>TRUE</code> and if confidence regions are available, the layer of <code>stat_conf3logit()</code> is added, otherwise only a <code>gg3logit()</code> object with the layer of <code>stat_field3logit()</code> is returned.   |

**See Also**

Other gg functions: [gg3logit\(\)](#), [stat\\_3logit\(\)](#), [stat\\_conf3logit\(\)](#), [stat\\_field3logit\(\)](#)

**Examples**

```
## Not run:
data(cross_1year)

mod0 <- nnet::multinom(employment_sit ~ gender + finalgrade, data = cross_1year)
field0 <- field3logit(mod0, 'genderFemale', conf = 0.95)

autoplot(field0)

## End(Not run)
```

---

cross\_1year

*Master's students' employment condition*

---

**Description**

data.frame with 3282 cross-sectional observations of 7 variables about employment condition of master's students one year after graduation. Data are used in Santi et al. (2019) and refer to students graduated at the University of Trento (Italy) between 2009 and 2013.

**Format**

data.frame with 3282 observations of 7 variables:

**employment\_sit:** employment situation, a factor with three levels: *Employed, Unemployed, Trainee*.

**gender:** gender, a factor with two levels: *Male, Female*.

**finalgrade:** final grade degree, a factor with three levels: *Low, Average, High*.

**duration:** duration of studies, a factor with three levels: *Short, Average, Long*.

**social\_class:** social class, a factor with five levels: *Working class, White-collar workers, Lower middle class, Upper middle class, Unclassified*.

**irregularity:** irregularity indicator of student's studies, a factor with three levels: *Low, Average, High*.

**hsscore:** high school final score, a numeric between 60 and 100.

**References**

Santi F, Dickson MM, Espa G (2019). "A graphical tool for interpreting regression coefficients of trinomial logit models." *The American Statistician*, **73**(2), 200-207. doi: [10.1080/00031305.2018.1442368](https://doi.org/10.1080/00031305.2018.1442368).

---

|               |   |
|---------------|---|
| extract3logit | <i>Extract information from fitted models</i> |
|---------------|---|

---

## Description

`extract3logit()` extracts all information which is relevant for computing the vector field(s) from the object passed to argument `x`. See **Details** for information on how new S3 methods of generic `extract3logit()` should be implemented.

## Usage

```
extract3logit(x, ...)  
  
## Default S3 method:  
extract3logit(x, ...)  
  
## S3 method for class 'clm'  
extract3logit(x, ...)  
  
## S3 method for class 'clm2'  
extract3logit(x, ...)  
  
## S3 method for class 'mlogit'  
extract3logit(x, ...)  
  
## S3 method for class 'model3logit'  
extract3logit(x, ...)  
  
## S3 method for class 'multinom'  
extract3logit(x, ...)  
  
## S3 method for class 'polr'  
extract3logit(x, ...)  
  
## S3 method for class 'vgam'  
extract3logit(x, ...)  
  
## S3 method for class 'vglm'  
extract3logit(x, ...)
```

## Arguments

|                  |  |
|------------------|--|
| <code>x</code>   | an object of any of the classes listed above. If instead, a list is passed, it should be structured as described in section <b>Details</b> . |
| <code>...</code> | other arguments passed to other methods.   |

## Details

When a specific method is not available for a fitted model, it is possible to pass a list to argument `x`. In that case, the list should consists of the following components (the order is irrelevant):

- `levels`: vector of possible values of the dependent variable. It should be a character vector of length three, whose first element is interpreted as the reference level, whereas the second and the third elements are associated to the first and second columns of matrix `B` respectively.
- `B`: matrix of regression coefficients. It should be a numeric matrix (or any coercible object) with two columns if the model is cardinal, with only one column if the model is ordinal. The number of rows should be equal to the number of covariates and the names of covariates should be added as row names. The intercepts should be included only in case of categorical models, whereas column names, if provided, are ignored.
- `alpha`: intercepts of ordinal models. It should be a numerical vector of length two if the model is ordinal, otherwise this component should be either set to `NULL` or missing.
- `vcovB`: covariance matrix of regression coefficients. It should be a numeric matrix (or any coercible object) where the number of rows and columns equals the number of elements of `B`. Rows and columns should be ordered according to the labels of the dependent variable (slower index), and then to the covariates (faster index).

If a new S3 method for generic `extract3logit()` has to be implemented, the following components may be set:

- `readfrom`: character with information about the function that returned the estimates in the form `package::function` (for example `nnet::multinom`, `MASS::polr`, ...)

**In any case**, once the list has been created, the new method should invoke the default method `extract3logit.default()` and return its output. By so doing, automatic checks and initialisations are run before the `model3logit` object is returned.

## Value

An object of class `model3logit`.

## See Also

`plot3logit-package`, `field3logit()`.

---

field3logit

*Computation of the vector field*

---

## Description

`field3logit()` computes the vector field associated to a change in regressor values (which may involve more than one regressor) of a trinomial logit model either fitted by some multinomial regression function or explicitly specified.



The method `plot()` draws the ternary plot using standard graphics methods provided by package Ternary. See functions `gg3logit()` and `autoplot()` for plotting through the package `ggtern` based on the grammar of graphics.

Methods `as.data.frame()`, `as_tibble()`, `fortify()` and `tidy()` permits the graphical information of a `field3logit` object to be exported in a standardised format (either a `data.frame` or a `tibble`).

## Usage

```
field3logit(  
  model,  
  delta,  
  label = "",  
  p0 = NULL,  
  nstreams = 8,  
  narrows = Inf,  
  edge = 0.01,  
  conf = NA,  
  npoints = 100,  
  alpha = deprecated(),  
  vcov = deprecated()  
)  
  
## S3 method for class 'field3logit'  
print(x, ...)  
  
## S3 method for class 'field3logit'  
plot(x, ..., add = FALSE, length = 0.05)  
  
## S3 method for class 'field3logit'  
as_tibble(x, ..., wide = TRUE)  
  
## S3 method for class 'field3logit'  
as.data.frame(x, ..., wide = TRUE)  
  
## S3 method for class 'field3logit'  
fortify(model, data, ..., wide = TRUE)  
  
## S3 method for class 'field3logit'  
tidy(x, ..., wide = TRUE)  
  
## S3 method for class 'field3logit'  
coef(object, ...)  
  
## S3 method for class 'field3logit'  
vcov(object, ...)  
  
## S3 method for class 'field3logit'
```

```

labels(object, ...)

## S3 replacement method for class 'field3logit'
labels(object) <- value

```

### Arguments

|           |  |
|-----------|--|
| model     | either a fitted trinomial model or a list properly structured. See section <b>Details</b> of <a href="#">extract3logit()</a> and the last example of <a href="#">plot3logit-package</a> .  |
| delta     | the change in the values of covariates to be represented. This could be either a numeric vector, the name of a covariate (passed either as a character or an expression), or a mathematical expression involving one or more than one covariates (passed either as a character or an expression). If a list is passed to delta, multiple fields are computed according to parameters passed as components of a 2-level list. See details and examples. |
| label     | label to be used for identifying the field when multiple fields are plotted. See <a href="#">multifield3logit()</a> .  |
| p0        | list of starting points (ternary coordinates) of the curves of the field. If not specified, field3logit automatically compute nstreams candidate points so that arrows are evenly distributed over the ternary plot area. See Examples.  |
| nstreams  | number of stream lines of the field to be computed. In case of ordinal models, this parameter is ineffective, as only one curve can be drawn. The parameter is ineffective also if argument p0 is set.   |
| narrows   | maximum number of arrows to be drawn per stream line.  |
| edge      | minimum distance between each arrow (or point) and the edge of the ternary plot.   |
| conf      | confidence level of confidence regions to be computed <b>for each arrow</b> of the vector field.   |
| npoints   | number of points of the border to be computed <b>for each confidence region</b> .  |
| alpha     | deprecated argument. It may be removed in a future version of the package.   |
| vcov      | deprecated argument. It may be removed in a future version of the package.   |
| x, object | object of class field3logit.   |
| ...       | other arguments passed to or from other methods.   |
| add       | logical argument which specifies whether the field should be added to an existing plot (add = TRUE) or a new ternary plot should be drawn (add = FALSE).   |
| length    | length of the edges of the arrow head (in inches).   |
| wide      | it allows to choose whether as.data.frame, as_tibble, fortify and tidy should return a data.frame or a tibble in wide (default) or long form.  |
| data      | not used. Argument included only for interface compatibility with the generic fortify.   |
| value     | value to be assigned.  |

## Details

Argument `delta` could be passed in one of the following formats:

- explicitly, as a numeric vector corresponding to the change  $\Delta x \in \mathbf{R}^k$  in regressors values  $x \in \mathbf{R}^k$ ;
- implicitly, as a character of the name of the covariate to be considered. In this case, vector  $\Delta x \in \mathbf{R}^k$  is computed for a unit change of the specified covariate;
- as a mathematical expression (passed as an expression or a character object) involving one or more than one covariates. This allows one to analyse the effects of composite covariate changes through an easy-to-write and easy-to-read code without having to cope with explicit numerical specification of vector  $\Delta x \in \mathbf{R}^k$ .

See examples for comparing all three methods.

**It is also possible to pass a list to argument `delta`.** In such a case, the function `field3logit` is run once for every component of `delta`, and the set of generated `field3logit` objects is combined into a single object of class `multifield3logit`. The components of the list passed to `delta` must be named lists whose elements are used as arguments of each call of function `field3logit`, whilst the arguments specified in the parent call of `field3logit` are used as default values. It follows that arguments shared by all fields can be specified once in the parent call of `field3logit`, and only arguments which changes from field to field (such as `delta` and `label`) should be set in the lists making up the list passed to `delta`. See the penultimate example in section `Examples` and the help of `multifield3logit()`.

**Finally**, when argument `delta` is a character, it is possible to indicate the name of a factor covariate between delimiters `<<`, `>>`. In that case, `field3logit()` creates a `multifield3logit` object where each field corresponds to the effect of each dummy generated by the factor regressor. If more than one regressor is included between delimiters `<<`, `>>`, all combinations between dummies are generated. See the last example in section **Examples**.

## Value

S3 object of class `field3logit` structured as a named list or an object of class `multifield3logit` if `delta` is a list or syntax `<<...>>` is used.

## See Also

`multifield3logit()`, `gg3logit()`, `autoplot()`.

## Examples

```
data(cross_1year)

## Not run:
# Fitting the model
mod0 <- nnet::multinom(employment_sit ~ finalgrade + irregularity + hsscore,
  cross_1year)
mod0

# Assessing the effect of "finalgradeHigh" (explicit notation)
field0 <- field3logit(mod0, c(0, 0, 1, 0, 0, 0))
```

```

gg3logit(field0) + stat_field3logit()

# Assessing the effect of "finalgradeHigh" (implicit notation)
field0 <- field3logit(mod0, 'finalgradeHigh')
gg3logit(field0) + stat_field3logit()

# Assessing the combined effect of "finalgradeHigh" and
# a decrease of "hsscore" by 10
field0 <- field3logit(mod0, 'finalgradeHigh - 10 * hsscore')
gg3logit(field0) + stat_field3logit()

## End(Not run)

# Fitting the model
mod1 <- nnet::multinom(employment_sit ~ ., data = cross_1year)

# List passed to argument "delta" for generating "multifield3logit" objects
refpoint <- list(c(0.7, 0.15, 0.15))
depo <- list(
  list(delta = 'durationShort', label = 'Short duration'),
  list(delta = 'durationLong', label = 'Long duration'),
  list(delta = 'finalgradeHigh', label = 'High final grade'),
  list(delta = 'finalgradeLow', label = 'Low final grade')
)
mfields <- field3logit(mod1, delta = depo, p0 = refpoint, narrows = 1)
mfields

# Syntax "<<...>>" for categorical covariates
mfields <- field3logit(
  model = mod1, delta = '<<finalgrade>>', label = 'Final grade',
  p0 = refpoint, narrows = 1
)
mfields

```

---

gg3logit

*Create a new gg3logit*


---

## Description

gg3logit initialises a [ggplot](#) object through [ggtern](#). If a field3logit or a multifield3logit object is passed to argument data, the mandatory aesthetics of the ternary plot are automatically set.

## Usage

```
gg3logit(data = NULL, mapping = aes(), ...)
```

**Arguments**

|         |  |
|---------|--|
| data    | a field3logit object, a multifold3logit object, or a data.frame structured like a fortified field3logit or a multifold3logit object.   |
| mapping | list of aesthetic mappings to be used for plot. If a field3logit or a multifold3logit is passed to data, none of the aesthetics mappings listed in section <i>Aesthetic mappings</i> below has to be specified (if specified, they will be overwritten). |
| ...     | additional arguments passed through to <code>ggtern</code> .   |

**Aesthetic mappings**

The following aesthetics are required by at least one of the available stats. None of them should be specified if a field3logit or a multifold3logit is passed to the argument data of `gg3logit()`, `stat_field3logit()` or `stat_conf3logit()`:

- x, y, z are required by:
  - `stat_field3logit()` as ternary coordinates of the starting points of the arrows;
  - `stat_conf3logit()` ternary coordinates of the points on the border of confidence regions;
- xend, yend, zend: required by `stat_field3logit()` as ternary coordinates of the ending points of the arrows;
- group: identifier of groups of graphical objects (arrows and their confidence regions);
- type: type of graphical object (arrows or confidence regions).

The following variables of a fortified field3logit or a multifold3logit object may be useful for defining other standard aesthetics (such as fill, colour, ...):

- label identifies a field through a label, thus it is useful for distinguishing the fields in a multifold3logit object.
- idarrow identifies each group of graphical objects (arrows and their confidence regions) *within* every field. Unlike variable group, idarrow is not a global identifier of graphical objects.

**See Also**

Other gg functions: `autoplot.field3logit()`, `stat_3logit()`, `stat_conf3logit()`, `stat_field3logit()`

**Examples**

```
## Not run:
data(cross_1year)

mod0 <- nnet::multinom(employment_sit ~ gender + finalgrade, data = cross_1year)
field0 <- field3logit(mod0, 'genderFemale')

gg3logit(field0) + stat_field3logit()

## End(Not run)
```

---

|        |   |
|--------|---|
| labels | <i>Set the labels of a field3logit or a multifield3logit object</i> |
|--------|---|

---

**Description**

It sets the labels of an existing field3logit or a multifield3logit object.

**Usage**

```
labels(object) <- value
```

**Arguments**

|        |  |
|--------|--|
| object | a field3logit or a multifield3logit object.                                      |
| value  | a character with the new label (or labels in case of a multifield3logit object). |

---

|                  |                                 |
|------------------|---------------------------------|
| multifield3logit | <i>Multiple trilogit fields</i> |
|------------------|---------------------------------|

---

**Description**

Methods of S3 class multifield3logit handle multiple fields3logit objects simultaneously and permit new multifield3logit objects to be easily created by means of the sum operator "+".

**Usage**

```
multifield3logit(x, ...)

## S3 method for class 'Hfield3logit'
x + y

## S3 method for class 'multifield3logit'
print(x, maxitems = 10, ...)

## S3 method for class 'multifield3logit'
plot(x, y = NULL, add = FALSE, col = NA, legend = TRUE, ...)

## S3 method for class 'multifield3logit'
as_tibble(x, ..., wide = TRUE)

## S3 method for class 'multifield3logit'
as.data.frame(x, ..., wide = TRUE)

## S3 method for class 'multifield3logit'
fortify(model, data, ..., wide = TRUE)
```

```
## S3 method for class 'multifield3logit'  
tidy(x, ..., wide = TRUE)  
  
## S3 method for class 'multifield3logit'  
labels(object, ...)  
  
## S3 replacement method for class 'multifield3logit'  
labels(object) <- value  
  
## S3 method for class 'multifield3logit'  
x[i, drop = TRUE]  
  
## S3 replacement method for class 'multifield3logit'  
x[i] <- value
```

### Arguments

|                                  |   |
|----------------------------------|---|
| <code>x, y, model, object</code> | object of class <code>field3logit</code> or <code>multifield3logit</code> .   |
| <code>...</code>                 | other arguments passed to or from other methods.  |
| <code>maxitems</code>            | maximum number of items to be enumerated when an object of class <code>multifield3logit</code> is printed.  |
| <code>add</code>                 | logical argument which specifies whether the field should be added to an existing plot ( <code>add = TRUE</code> ) or a new ternary plot should be drawn ( <code>add = FALSE</code> ).  |
| <code>col, legend</code>         | graphical parameters if Ternary package is used.  |
| <code>wide</code>                | it allows to choose whether <code>as.data.frame</code> , <code>as_tibble</code> , <code>fortify</code> and <code>tidy</code> should return a <code>data.frame</code> or a <code>tibble</code> in wide (default) or long form. |
| <code>data</code>                | not used. Argument included only for interface compatibility with the generic <code>fortify</code> .  |
| <code>value</code>               | value to be assigned.   |
| <code>i</code>                   | index of the <code>field3logit</code> object to be selected.  |
| <code>drop</code>                | if <code>TRUE</code> , a <code>field3logit</code> object is returned if the subsetted <code>multifield3logit</code> object has length one.  |

### Value

S3 object of class `multifield3logit` structured as a named list.

### See Also

[field3logit\(\)](#).

**Examples**

```
## Not run:
data(cross_1year)

mod0 <- nnet::multinom(employment_sit ~ ., data = cross_1year)
mod0

field_Sdur <- field3logit(mod0, 'durationShort',
  label = 'Short duration')
field_Hfgr <- field3logit(mod0, 'finalgradeHigh',
  label = 'High final grade')

gg3logit(field_Sdur + field_Hfgr) +
  stat_field3logit()
  facet_wrap(~ label)

refpoint <- list(c(0.7, 0.15, 0.15))

field_Sdur <- field3logit(mod0, 'durationShort',
  label = 'Short duration', p0 = refpoint, narrows = 1)
field_Ldur <- field3logit(mod0, 'durationLong',
  label = 'Long duration', p0 = refpoint, narrows = 1)
field_Hfgr <- field3logit(mod0, 'finalgradeHigh',
  label = 'High final grade', p0 = refpoint, narrows = 1)
field_Lfgr <- field3logit(mod0, 'finalgradeLow',
  label = 'Low final grade', p0 = refpoint, narrows = 1)

mfields <- field_Sdur + field_Ldur + field_Lfgr + field_Hfgr
mfields

gg3logit(mfields) +
  stat_field3logit(aes(colour = label)) +
  theme_zoom_L(0.45)

## End(Not run)
```

---

stat\_3logit

*Add a field and confidence regions to a gg3logit plot*


---

**Description**

`stat_3logit()` adds a field and confidence regions to a `gg3logit` plot. `stat_3logit()` is a wrapper for stats `stat_field3logit()` and `stat_conf3logit()` which are jointly applied.

**Usage**

```
stat_3logit(
  mapping_field = aes(),
```



```

mapping_conf = aes(),
data = NULL,
params_field = list(),
params_conf = list(),
show.legend = NA,
inherit.aes = TRUE,
conf = TRUE
)

```

### Arguments

|                             |   |
|-----------------------------|---|
| mapping_field, mapping_conf | aesthetic mappings passed to argument mapping of <code>stat_field3logit()</code> and <code>stat_conf3logit()</code> .   |
| data                        | a <code>field3logit</code> object, a <code>multifield3logit</code> object, or a <code>data.frame</code> structured like a fortified <code>field3logit</code> or a <code>multifield3logit</code> object.   |
| params_field, params_conf   | graphical parameters passed to argument mapping of <code>stat_field3logit()</code> and <code>stat_conf3logit()</code> .   |
| show.legend                 | logical. Should this layer be included in the legends? NA, the default, includes if any aesthetics are mapped. FALSE never includes, and TRUE always includes. It can also be a named logical vector to finely select the aesthetics to display.              |
| inherit.aes                 | If FALSE, overrides the default aesthetics, rather than combining with them. This is most useful for helper functions that define both data and aesthetics and shouldn't inherit behaviour from the default plot specification, e.g. <code>borders()</code> . |
| conf                        | if TRUE and if confidence regions are available, the layer of <code>stat_conf3logit()</code> is added, otherwise only the layer of <code>stat_field3logit()</code> is returned.   |

### See Also

Other gg functions: `autoplot.field3logit()`, `gg3logit()`, `stat_conf3logit()`, `stat_field3logit()`

### Examples

```

## Not run:
data(cross_1year)

mod0 <- nnet::multinom(employment_sit ~ gender + finalgrade, data = cross_1year)
field0 <- field3logit(mod0, 'genderFemale', conf = 0.95)

gg3logit(field0) + stat_3logit()
gg3logit(field0) + stat_3logit(conf = TRUE)

## End(Not run)

```

---

|                 |   |
|-----------------|---|
| stat_conf3logit | <i>Add the confidence regions of a field to a gg3logit plot</i> |
|-----------------|---|

---

### Description

`stat_conf3logit()` adds a field to a `gg3logit` plot.

### Usage

```
stat_conf3logit(
  mapping = aes(),
  data = NULL,
  geom = "polygon",
  position = "identity",
  show.legend = NA,
  inherit.aes = TRUE,
  ...
)
```

### Arguments

|             |  |
|-------------|--|
| mapping     | list of aesthetic mappings to be used for plot. Mandatory aesthetics should not be specified if <code>field3logit</code> or <code>multifield3logit</code> object is passed to <code>data</code> . See section <b>Aesthetic mappings</b> of <code>gg3logit()</code> for details.          |
| data        | a <code>field3logit</code> object, a <code>multifield3logit</code> object, or a <code>data.frame</code> structured like a fortified <code>field3logit</code> or a <code>multifield3logit</code> object.  |
| geom        | The geometric object to use display the data   |
| position    | Position adjustment, either as a string, or the result of a call to a position adjustment function.  |
| show.legend | logical. Should this layer be included in the legends? <code>NA</code> , the default, includes if any aesthetics are mapped. <code>FALSE</code> never includes, and <code>TRUE</code> always includes. It can also be a named logical vector to finely select the aesthetics to display. |
| inherit.aes | If <code>FALSE</code> , overrides the default aesthetics, rather than combining with them. This is most useful for helper functions that define both data and aesthetics and shouldn't inherit behaviour from the default plot specification, e.g. <code>borders()</code> .              |
| ...         | additional arguments passed through to <code>ggtern</code> .   |

### See Also

Other gg functions: `autoplot.field3logit()`, `gg3logit()`, `stat_3logit()`, `stat_field3logit()`

**Examples**

```
## Not run:
data(cross_1year)

mod0 <- nnet::multinom(employment_sit ~ gender + finalgrade, data = cross_1year)
field0 <- field3logit(mod0, 'genderFemale', conf = 0.95)

gg3logit(field0) + stat_conf3logit()
gg3logit(field0) + stat_field3logit() + stat_conf3logit()

## End(Not run)
```

---

|                  |                                       |
|------------------|---------------------------------------|
| stat_field3logit | <i>Add a field to a gg3logit plot</i> |
|------------------|---------------------------------------|

---

**Description**

`stat_field3logit()` adds a field to a `gg3logit` plot.

**Usage**

```
stat_field3logit(
  mapping = aes(),
  data = NULL,
  geom = "segment",
  position = "identity",
  show.legend = NA,
  inherit.aes = TRUE,
  arrow. = arrow(length = unit(0.2, "cm")),
  ...
)
```

**Arguments**

|             |   |
|-------------|---|
| mapping     | list of aesthetic mappings to be used for plot. Mandatory aesthetics should not be specified if <code>field3logit</code> or <code>multifield3logit</code> object is passed to data. See section <b>Aesthetic mappings</b> of <code>gg3logit()</code> for details. |
| data        | a <code>field3logit</code> object, a <code>multifield3logit</code> object, or a <code>data.frame</code> structured like a fortified <code>field3logit</code> or a <code>multifield3logit</code> object.   |
| geom        | The geometric object to use display the data  |
| position    | Position adjustment, either as a string, or the result of a call to a position adjustment function.   |
| show.legend | logical. Should this layer be included in the legends? NA, the default, includes if any aesthetics are mapped. FALSE never includes, and TRUE always includes. It can also be a named logical vector to finely select the aesthetics to display.                  |

`inherit.aes` If FALSE, overrides the default aesthetics, rather than combining with them. This is most useful for helper functions that define both data and aesthetics and shouldn't inherit behaviour from the default plot specification, e.g. `borders()`.

`arrow.` specification for arrow heads, as created by function `arrow` of package `grid`.

`...` additional arguments passed through to `ggtern`.

### See Also

Other gg functions: `autoplot.field3logit()`, `gg3logit()`, `stat_3logit()`, `stat_conf3logit()`

### Examples

```
## Not run:
data(cross_1year)

mod0 <- nnet::multinom(employment_sit ~ gender + finalgrade, data = cross_1year)
field0 <- field3logit(mod0, 'genderFemale', conf = 0.95)

gg3logit(field0) + stat_field3logit()
gg3logit(field0) + stat_field3logit() + stat_conf3logit()

## End(Not run)
```

---

TernaryField

*Draw a field on an existing ternary plot*

---

### Description

`TernaryField()` adds the vector field returned by `field3logit()` to an existing ternary plot generated by `Ternary::TernaryPlot()`.

### Usage

```
TernaryField(
  field,
  ...,
  length = 0.05,
  conf = FALSE,
  npoints = 100,
  conf.args = list()
)
```

**Arguments**

|           |   |
|-----------|---|
| field     | object of class <code>field3logit</code> as returned by <code>field3logit()</code> .  |
| ...       | other arguments passed to or from other methods.  |
| length    | length of the edges of the arrow head (in inches).  |
| conf      | if FALSE confidence regions are not drawn, even if available; if TRUE confidence regions are drawn only if available; if a numeric value is passed, confidence regions at the specified confidence level are computed (if not already available) and drawn. |
| npoints   | number of points of the border to be computed <b>for each confidence region</b> .   |
| conf.args | graphical parameters of confidence regions to be passed to <code>Ternary::TernaryPolygon()</code> .   |

**Value**

An object of class `field3logit` with confidence regions included, if computed within `TernaryField()`.

**See Also**

`field3logit()`.

**Examples**

```
library(nnet)
data(cross_1year)

mod0 <- nnet::multinom(employment_sit ~ gender + finalgrade, data = cross_1year)
field0 <- field3logit(mod0, 'genderFemale')

TernaryPlot()
TernaryField(field0)
```

**Description**

Self-reported votes from 2016 VOTER Survey by Democracy Fund Voter Study Group (2017). Object `USvote2016` includes only few variables based on the result of the survey, which are publicly available online. See file `"data-raw/USvote2016_prepare.R"` in the GitHub repository `"f-santi/plot3logit"` (<https://github.com/f-santi/plot3logit>), where it is documented how the dataset `USvote2016` has been generated.

**Format**

tibble (data.frame) with 8000 observations of 7 variables:

**idcode:** voter identifier (integer).

**vote:** declared vote, a factor with three levels: *Clinton, Trump, Other*.

**race:** race, a factor with six levels: *White, Black, Hispanic, Asian, Mixed, Other*.

**educ:** level of education, a factor with six levels: *No high school, High school grad., Some college, 2-year college, 4-year college, Post-grad*.

**gender:** gender, a factor with four levels: *Male, Female, Skipped, Not Asked*.

**birthyr:** decades when the voter was born, a factor with six levels: *[1920,1940), [1940,1950), [1950,1960), [1960,1970), [1970,1980), [1980,2000)*.

**famincome:** income (in USD) of voter's family, a factor with five levels: *[0; 30,000), [30,000; 60,000), [60,000; 100,000), [100,000; 150,000), [150,000; Inf)*.

**References**

Democracy Fund Voter Study Group (2017). "Views of the electorate research survey, December 2016." <https://www.voterstudygroup.org>.

# Index

- \* **data**
  - cross\_1year, 6
  - USvote2016, 21
- \* **gg functions**
  - autoplot.field3logit, 5
  - gg3logit, 12
  - stat\_3logit, 16
  - stat\_conf3logit, 18
  - stat\_field3logit, 19
- + .Hfield3logit (multifield3logit), 14
- [.multifield3logit (multifield3logit), 14
- [<- .multifield3logit (multifield3logit), 14
  
- add\_confregions, 4
- arrow, 20
- as.data.frame(), 9
- as.data.frame.field3logit (field3logit), 8
- as.data.frame.multifield3logit (multifield3logit), 14
- as\_tibble(), 9
- as\_tibble.field3logit (field3logit), 8
- as\_tibble.multifield3logit (multifield3logit), 14
- autoplot(), 2, 5, 9, 11
- autoplot.field3logit, 5, 13, 17, 18, 20
  
- borders(), 17, 18, 20
  
- clm, 3
- clm2, 3
- coef.field3logit (field3logit), 8
- cross\_1year, 6
  
- extract3logit, 7
- extract3logit(), 2, 3, 7, 8, 10
- extract3logit.default(), 8
  
- field3logit, 8
  
- field3logit(), 3, 8, 11, 15, 20, 21
- fortify(), 9
- fortify.field3logit (field3logit), 8
- fortify.multifield3logit (multifield3logit), 14
  
- gg3logit, 5, 6, 12, 16–20
- gg3logit(), 3, 5, 9, 11, 13, 18, 19
- ggplot, 12
- ggplot2, 2
- ggtern, 2, 9, 12, 13, 18, 20
- grid, 20
  
- labels, 14
- labels.field3logit (field3logit), 8
- labels.multifield3logit (multifield3logit), 14
- labels<- (labels), 14
- labels<- .field3logit (field3logit), 8
- labels<- .multifield3logit (multifield3logit), 14
  
- mlogit, 3
- multifield3logit, 14
- multifield3logit(), 10, 11
- multinom, 3
  
- plot, 2
- plot(), 2, 9
- plot.field3logit (field3logit), 8
- plot.multifield3logit (multifield3logit), 14
- plot3logit-package, 2
- polr, 3
- print.field3logit (field3logit), 8
- print.multifield3logit (multifield3logit), 14
  
- stat\_3logit, 6, 13, 16, 18, 20
- stat\_3logit(), 5, 16
- stat\_conf3logit, 6, 13, 17, 18, 20

`stat_conf3logit()`, [2](#), [5](#), [13](#), [16–18](#)  
`stat_field3logit`, [6](#), [13](#), [17](#), [18](#), [19](#)  
`stat_field3logit()`, [5](#), [13](#), [16](#), [17](#), [19](#)

`Ternary::TernaryPlot()`, [20](#)  
`Ternary::TernaryPolygon()`, [21](#)  
`TernaryField`, [20](#)  
`TernaryField()`, [2](#), [3](#), [20](#), [21](#)  
`tidy()`, [9](#)  
`tidy.field3logit (field3logit)`, [8](#)  
`tidy.multifield3logit`  
    (`multifield3logit`), [14](#)

`USvote2016`, [21](#)

`vcov.field3logit (field3logit)`, [8](#)  
`vgam`, [3](#)  
`vglm`, [3](#)